



## DECLARATION OF PERFORMANCE No. 181-CPR-2024

1. Unique identification code:

Self-adhesive membrane

### NEXLER Membrana SP (2024/1)

2. Intended use or uses:

- a) Damp proofing in buildings, including basement tanking subject to reaction to fire
- b) Damp-proofing in buildings, including basement tanking

3. The manufacturer:

**NEXLER sp. z o.o.**  
ul. Łużycka 6 81-537 Gdynia, Poland  
tel., fax +48 58 781 45 85  
e-mail: info@nexler.com

4. Systems of assessment and verification of constancy of performance:

**system 2+ – for the applications: b**  
**system 3 – for the applications: a**

5. Harmonized standard:

EN 13967:2012

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification (Polskie Centrum Badań i Certyfikacji S.A.),

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Reaction to fire	class E	EN 13967:2012
Watertightness	60 kPa (method B)	
Tensile properties during stretching: - longitudinal - extension	≥ 200 N/50 mm ≥ 100 %	
- transversal - extension	≥ 200 N/50 mm ≥ 100 %	
Resistance to static loading	≥ 10 kg (meth. B)	
Resistance to impact	≥ 350 mm (meth. A)	
Resistance to Tearing: - longitudinal - transversal	≥ 130 N ≥ 130 N	
Resistance of the Joint: - longitudinal - transversal	≥ 200 N/50 mm ≥ 200 N/50 mm	
Durability - durability after artificial ageing, watertightness	≥ 60kPa (method B)	
- durability against chemical	≥ 60kPa (method B)	
Dangerous substances	NPD	

The performance of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:  
Konrad Liberda

  
Konrad Liberda

Gdynia, 24.01.2021

