



DECLARATION OF PERFORMANCE No. 194-CPR-2024

1. Unique identification code:

Heat-weldable top layer bitumen membrane

NEXLER Protection (2024/1)

2. Intended use or uses:

- waterproofing of roofs, which is the subject to fire reaction test,
- waterproofing of roofs,
- waterproofing of roofs, which is the subject to test of resistance to external fire exposure.

3. The manufacturer:

NEXLER sp. z o.o.
ul. Łużycka 6, 81-537 Gdynia, Poland
tel., fax +48 58 781 45 85
e-mail: info@nexler.com

4. Systems of assessment and verification of constancy of performance:

system 2+ – for the applications: b
system 3 – for the applications: a, c

5. Harmonized standard:

EN 13707:2004+A2:2009

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification
(Polskie Centrum Badań i Certyfikacji S.A.)

1488 Building Research Institute (Instytut Techniki Budowlanej).

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Resistance to external fire exposure	B _{roof} (t ₁), B _{roof} (t ₂).	EN 13707:2004+A2:2009
Reaction to fire	class E	
Watertightness	≥ 10 kPa (method A)	
Maximum tensile force: - longitudinal - extension	1100 ± 200 N/50 mm (50 ± 10) %	
- transverse - extension	900 ± 200 N/50 mm (50 ± 10) %	
Resistance to root penetration	NPD	
Resistance to static loading	≥ 20 kg (method A)	
Resistance to impact	≥ 1750 mm (method A)	
Resistance to Tearing Longitudinal Transversal	350 ± 150 N 350 ± 150 N	
Resistance of the joint Shear strength Longitudinal joint Transversal joint	900 ± 200 N/50 mm 950 ± 250 N/50 mm	
Tear off strength Longitudinal joint Transversal joint	150 ± 100 N/50 mm 150 ± 100 N/50 mm	
Durability: flow resistance in high temperature	(100 ± 10) °C	
Flexibility	≤ -25 °C	
Dangerous substances	NPD	

The performances of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Konrad Liberda


Kierownik Biura Produktowej
Wsparcia Technicznego
Konrad Liberda

Gdynia, 21.02.2024

6. Declared performance:



NEXLER Sp. z o.o.
81-537 Gdynia
ul. Łużycka 6

tel.: +48 58 781 45 85
e-mail: info@nexler.com

NIP: 586-20-73-821
Regon 191528483
nr rej. BDO: 000009205

Sąd Rejonowy Gdańsk-Północ w Gdańsku
VIII Wydz. Gospodarczy KRS 000063616
Kapitał zakładowy 7 772 500,00 Pln