



DECLARATION OF PERFORMANCE No. 189-CPR-2024

1. Unique identification code:

Heat-weldable top layer bitumen membrane

NEXLER PREMIUM PYE PV200 S40H (2024/1)

2. Intended use or uses:

- waterproofing of roofs, which is the subject to fire reaction test,
- waterproofing of roofs,
- waterproofing of roofs, which is the subject to test of resistance to external fire exposure.

3. The manufacturer:

NEXLER sp. z o.o.
ul. Łużycka 2, 81-537 Gdynia, Poland
tel., fax +48 58 781 45 85
e-mail: info@nexler.com

4. Systems of assessment and verification of constancy of performance:

system 2+ – for the applications: b
system 3 – for the applications: a, c

5. Harmonized standard:

EN 13707:2004+A2:2009– for the applications:
a, b, c.

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification
(Polskie Centrum Badań i Certyfikacji S.A.)

1488 Building Research Institute (Instytut Techniki
Budowlanej), a Notified Body

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Resistance to external fire exposure	$B_{\text{roof}(t_1)}$, $B_{\text{roof}(t_2)}$	EN 13707:2004+A2:2009
Reaction to fire	class E	
Watertightness	≥ 10 kPa (metoda A)	
Maximum tensile force: - longitudinal - extension	850 ± 250 N/50 mm (50 ± 15) %	
- transverse - extension	600 ± 200 N/50 mm (50 ± 15) %	
Resistance to root penetration	NPD	
Resistance to static loading	NPD	
Resistance to impact	NPD	
Tear resistance	NPD	
Joint strength	NPD	
Durability: flow resistance at elevated temperature	(100 ± 10) °C	
Flexibility	≤ -20 °C	
Dangerous substances	NPD	

The performances of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Konrad Liberda

NEXLER
Kierownik Grupy Produktowej
i Wspierania Technicznego
Konrad Liberda

Gdynia, 11.01.2024

