

## DECLARATION OF PERFORMANCE No. 648-CPR-2021

1. Unique identification code of the product-type: Nexler EPOLIS EP-100 01

2. Intended use/es: **Physical resistance.** 

3. Manufacturer: NEXLER sp. z o.o. ul. Łużycka 6, 81-537 Gdynia, Poland tel., fax +48 58 781 45 85 www.nexler.com

4. Sysem/s of AVCP:

## System 4, System 3

5. Harmonised standard:

## EN 1504-2:2004

Notified body/ies:

## Instytut Techniki Budowlanej, nr 1488

Essential characteristics	Performance
Linear shrinkage	NPD
Compressive strength	NPD
Coefficient of thermal expansion	NPD
Abrasion resistance	< 3000 mg
Cross cut	NPD
Capillary absorption and permeability to water	< 0,1 kg/m <sup>2</sup> × h <sup>0,5</sup>
Thermal compatibility	NPD
Resistance to thermal shock	NPD
Crack bridging ability	NPD
Impact resistance	Class 1
Adhesion strength by pull off test	≥ 2,0 (1,5)ª N/mm²
Reaction to fire	B <sub>fl</sub> -s1
Skid resistance	NPD
Artificial weathering	NPD
Antistatic behaviour	NPD
Adhesion on wet concrete	NPD
Dangerous substances	NPD

<sup>a</sup>The value in brackets is the lowest accepted value of any reading.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Dawid Debski at Gdynia on 25.10.2023. (3rd edition)

dyrektor ds. badań 26f drinz. Dawid Debski

