

according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Nexler EPOLIS EP-400 UV składnik B

Substance / mixture mixtur

UFI AXUJ-J00Y-P00C-R5C2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

For the construction of a wide range of resin flooring systems laid on a concrete substrate. It can be used both as a primer, putty, leveling primer or topcoat.

Main intended use

PC-CON-5 Construction chemicals

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name IZOHAN sp. z o.o.

Address Łużycka 2, Gdynia, 81-963

Poland

Identification number (CRN)191528483VAT Reg NoPL5862073821Phone+48 58 781 45 85E-mailinfo@izohan.euWeb addresswww.izohan.eu

Competent person responsible for the safety data sheet

Name IZOHAN sp. z o.o. E-mail info@izohan.eu

1.4. Emergency telephone number

National Health Service (NHS) 111

National poisoning information centre Scotland, NHS 24: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Acute Tox. 4, H302 Skin Corr. 1C, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse effects on human health and the environment

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram



Signal word

Danger



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

Hazardous substances

benzvl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-057-00-5 CAS: 100-51-6 EC: 202-859-9 Registration number: 01-2119492630-38	benzyl alcohol	25-50	Acute Tox. 4, H302+H332 Eye Irrit. 2, H319	
Index: 612-067-00-9 CAS: 2855-13-2 EC: 220-666-8 Registration number: 01-2119514687-32	3-aminomethyl-3,5,5- trimethylcyclohexylamine	25-50	Acute Tox. 4, H302+H312 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412 Specific concentration limit: ATE Oral = 1030 mg/kg bw Skin Sens. 1A, H317: C ≥ 0,001 %	
CAS: 38294-64-3 EC: 500-101-4 Registration number: 01-2119965165-33	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine	25-50	Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412	1

Notes

1 Substance of unknown or variable composition, complex reaction products or biological materials - UVCB.



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Depending on the situation, call the medical rescue service and always ensure medical treatment. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Rinse skin with water or shower. Rinse cautiously with water for several minutes.

If in eves

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

RINSE THE MOUTH WITH WATER IMMEDIATELY AND LET THE PERSON DRINK 2-5 dl of cold water to reduce the heating effect of the corrosive substance. Consuming larger amounts of liquid is not advisable as it may induce vomiting and potential inhaling of the corrosive substances in the lungs. The affected person must not be forced to drink, particularly if already feeling pain in the mouth or throat. In this case let the affected person only rinse the mouth with water. DO NOT PROVIDE ACTIVATED CARBON! Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system.

If on skin

Causes severe skin burns. May cause an allergic skin reaction.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Storage temperature required between +10 ° C and +25 ° C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

DNEL

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	0.073 mg/m ³	Local chronic effects	
Workers	Inhalation	0.073 mg/m ³	Local acute effects	
Consumers	Oral	0.526 mg/kg bw/day	Systemic chronic effects	

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	0.493 mg/m ³	Systemic chronic effects	
Workers	Dermal	0.14 mg/kg bw/day	Systemic chronic effects	
Consumers	Inhalation	0.074 mg/m ³	Systemic chronic effects	
Consumers	Dermal	0.050 mg/kg bw/day	Systemic chronic effects	
Consumers	Oral	0.050 mg/kg bw/day	Systemic chronic effects	



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

benzyl alcohol

Workers / consumers	Route of exposure	Value	Effect	Determining method
Workers	Inhalation	22 mg/m ³	Systemic chronic effects	
Workers	Inhalation	110 mg/m ³	Systemic acute effects	
Workers	Dermal	8 mg/kg bw/day	Systemic chronic effects	
Workers	Dermal	40 mg/kg bw/day	Systemic acute effects	
Consumers	Inhalation	5.4 mg/m ³	Systemic chronic effects	
Consumers	Inhalation	27 mg/m ³	Systemic acute effects	
Consumers	Dermal	4 mg/kg bw/day	Systemic chronic effects	
Consumers	Dermal	20 mg/kg bw/day	Systemic acute effects	
Consumers	Oral	4 mg/kg bw/day	Systemic chronic effects	
Consumers	Oral	20 mg/kg bw/day	Systemic acute effects	

PNEC

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Value	Determining method
Drinking water	0.06 mg/l	
Seawater	0.006 mg/l	
Water (intermittent release)	0.23 mg/l	
Microorganisms in wastewater treatment plants	3.18 mg/l	
Freshwater sediment	5.784 mg/kg of dry substance of sediment	
Sea sediments	0.578 mg/kg of dry substance of sediment	
Soil (agricultural)	1.121 mg/kg of dry substance of soil	

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Value	Determining method
Drinking water	0.011 mg/l	
Water (intermittent release)	0.111 mg/l	
Seawater	0.001 mg/l	
Microorganisms in wastewater treatment plants	10 mg/l	
Freshwater sediment	4320 mg/kg of dry substance of sediment	
Sea sediments	432 mg/kg of dry substance of sediment	
Soil (agricultural)	864 mg/kg of dry substance of soil	
Food chain	1 mg/kg of food	

benzyl alcohol

Route of exposure	Value	Determining method
Drinking water	1 mg/l	
Seawater	0.1 mg/l	



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

benzyl alcohol

Route of exposure	Value	Determining method
Water (intermittent release)	2.3 mg/l	
Microorganisms in wastewater treatment plants	39 mg/l	
Freshwater sediment	5.27 mg/kg of dry substance of sediment	
Sea sediments	0.527 mg/kg of dry substance of sediment	
Soil (agricultural)	0.456 mg/kg of dry substance of soil	

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid

Colour colourless, yellow

color intensity light

Odour characteristic

Melting point/freezing point data not available

Boiling point or initial boiling point and boiling range data not available Flammability data not available

Lower and upper explosion limit data not available
Flash point data not available
Auto-ignition temperature data not available
Decomposition temperature data not available

pH 11 (10% solution)
Kinematic viscosity >20,5 mm²/s at 40 °C

Solubility in water partially soluble
Solubility in other solvents partially soluble dissolves in most organic solvents

Partition coefficient n-octanol/water (log value) data not available Vapour pressure data not available

Density and/or relative density

Density 1 g/cm³

Relative vapour density data not available Particle characteristics data not available

9.2. Other information

not available



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with peroxides, aldehydes, ketones, epoxy resins.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Reactive metals (e.g. sodium, calcium, zinc, etc.). Substances which react with hydroxyl compounds. Organic acids (e.g. acetic acid, citric acid, etc.). Mineral acid. Sodium chlorate. The product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides can rapidly decompose the peroxide and create an explosion hazard. Oxidizers.

10.6. Hazardous decomposition products

As a result of thermal decomposition or reactions with incompatible substances, compounds such as nitric acid, ammonia, nitrogen oxides, aldehydes may be formed. Nitrogen oxides can react with water vapor to form caustic nitric acid.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Harmful if swallowed.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex
Oral	LD50	OECD 401	1030 mg/kg bw		Rat (Rattus norvegicus)	М
Inhalation (aerosols)	LC50	EPA OPPTS 870.1300	>5.01 mg/l of air	4 hour	Rat (Rattus norvegicus)	F/M
Dermal	LD ₅ 0	OECD 402	>2000 mg/kg bw	24 hour	Rat (Rattus norvegicus)	F/M
Oral	ATE		1030 mg/kg bw			

benzyl alcohol

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex
Oral	LD50		1620 mg/kg bw		Rat (Rattus norvegicus)	М
Inhalation	LD50	OECD 403	>4.178 mg/l of air	4 hour	Rat (Rattus norvegicus)	F/M
Dermal	LD ₅₀	EPA OTS 798.1100	>2000 mg/kg bw	24 hour	Rabbit	F/M

Skin corrosion/irritation

Causes severe skin burns and eye damage.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Result	Method	Time of exposure	Species	Source
Dermal	Corrosive		24 hour	Rabbit	



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Result	Method	Time of exposure	Species	Source
Dermal	Corrosive	OECD 431	1 hour	Human	in vitro, EpiDerm™

benzyl alcohol

Route of exposure	Result	Method	Time of exposure	Species	Source
Dermal	Slightly irritating	OECD 404	4 hour	Rabbit	

Serious eye damage/irritation

Causes severe skin burns and eye damage. Causes serious eye damage.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Result	Method	Time of exposure	Species
Eye	Corrosive, Serious eye damage	OECD 405		Rabbit

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Result	Method	Time of exposure	Species
Eye	Corrosive, Serious eye damage			

benzyl alcohol

Route of exposure	Result	Method	Time of exposure	Species
Eye	Irritating	OECD 405	24 hour	Rabbit

Respiratory or skin sensitisation

May cause an allergic skin reaction.

 $3\hbox{-} aminomethyl\hbox{-} 3,5,5\hbox{-} trimethyl cyclohexylamine}\\$

Route of exposure	Result	Method	Time of exposure	Species	Sex
Dermal	Sensitizing	OECD 406	24 hour	Guinea-pig (Cavia aperea f. porcellus)	М

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Result	Method	Time of exposure	Species	Sex
Dermal	Sensitizing				

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Repeated dose toxicity

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Parameter	Result	Method	Value	Time of exposure	Species	Sex
Oral	NOAEL	Systemic effects	OECD 408	59 mg/kg bw/day	13 week	Rat (Rattus norvegicus)	F/M

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Parameter	Result	Method	Value	Time of exposure	Species	Sex
Oral	NOAEL	Systemic effects	OECD 408	10 mg/kg bw/day	90 day	Rat (Rattus norvegicus)	F/M

benzyl alcohol

Route of exposure	Parameter	Result	Method	Value	Time of exposure	Species	Sex
Oral	NOAEL	Systemic effects	OECD 451	400 mg/kg bw/day	103 week	Rat (Rattus norvegicus)	F/M
Inhalation (aerosols)	NOAEC	Local effects, Systemic effects	OECD 412	1072 mg/m³ of air	4 week	Rat (Rattus norvegicus)	F/M

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Harmful to aquatic life with long lasting effects.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Time of exposure	Species	Environmen t
LC50		110 mg/l	96 hour	Fishes (Leuciscus idus)	
EC50	OECD 202	23 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	
ErC₅o	EU C.3 (87/302/EEC)	>50 mg/l	72 hour	Algae (Desmodesmus subspicatus)	
NOEC		1120 mg/l	18 hour	Aquatic microorganisms (Pseudomonas putida)	



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020 Revision date 07th April 2022

Version 2.1

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Time of exposure	Species	Environmen t
NOEC	EU C.3 (87/302/EEC)	11.2 mg/l	72 hour	Algae (Desmodesmus subspicatus)	

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Time of exposure	Species	Environmen t
LL 50	OECD 203	70.7 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
EL 50	OECD 202	11.1 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	
EL 50	OECD 201	79.4 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
NOELR	OECD 201	3.1 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	

benzyl alcohol

Parameter	Method	Value	Time of exposure	Species	Environmen t
LC50	EPA OPP 72-1	460 mg/l	96 hour	Fishes (Pimephales promelas)	
EC ₅ 0	OECD 202	230 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	
EC50	OECD 201	770 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
NOEC	OECD 201	310 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
IC50		390 mg/l	24 hour	Aquatic microorganisms (Nitrosomonas)	

Chronic toxicity

 $3\hbox{-} aminomethyl\hbox{-} 3,5,5\hbox{-} trimethyl cyclohexylamine}\\$

Parameter	Method	Value	Time of exposure	Species	Environmen t
NOEC	OECD 202	3 mg/l	21 day	Aquatic invertebrates (Daphnia magna)	

benzyl alcohol

Parameter	Method	Value	Time of exposure	Species	Environmen t
NOEC	OECD 211	51 mg/l	21 day	Aquatic invertebrates (Daphnia magna)	

12.2. Persistence and degradability



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

Biodegradability

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Time of exposure	Environment	Result
		8 %	/	Activated sludge	Hardly biodegradable

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Time of exposure	Environment	Result
	OECD 301F	0 %	28 day		Not biodegradable

benzyl alcohol

Parameter	Method	Value	Time of exposure	Environment	Result
	OECD 301A	95-97 %	21 day		Easily biodegradable

not available

12.3. Bioaccumulative potential

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Time of exposure	Species	Environment	Surrounding temperature [°C]
Log Pow	OECD 107	0.99				23°C

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Time of exposure	Species	 Surrounding temperature [°C]
Log Pow		3.6			25°C

benzyl alcohol

Parameter	Method	Value	Time of exposure	Species	Environment	Surrounding temperature [°C]
Log Pow		1.05				20°C

Bioaccumulation is not expected.

12.4. Mobility in soil

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Environment	Surrounding temperature
Koc		928		20°C

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Environment	Surrounding temperature
Log Koc	OECD 121	6.59		30°C

benzyl alcohol

Parameter	Method	Value	Environment	Surrounding temperature
Koc		15.7		20°C



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 Version 2.1

Contamination of water courses may occur in the event of rain.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Danger of environmental contamination, follow the applicable waste disposal regulations. Store unused product and contaminated packaging in closed containers for waste collection and hand over for disposal to a specialized company authorized to conduct such activity. Do not pour unused product into drains. It must not be disposed of together with municipal waste. Empty packaging can be used for energy in a waste incineration plant or collected in a landfill with an appropriate classification. Perfectly cleaned packaging can be recycled. The classification of waste may change depending on where it is generated.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

16 03 05 organic wastes containing hazardous substances *

Packaging waste type code

15 01 10 packaging containing residues of or contaminated by hazardous substances *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 2735

14.2. UN proper shipping name

AMINES, LIQUID, CORROSIVE, N.O.S. (contains: 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es)

8 Corrosive substances

14.4. Packing group

III - substances presenting low danger

14.5. Environmental hazards

No.

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code

Safety signs



-





according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020

Revision date 07th April 2022 2.1 Version

Road transport - ADR

Special provisions 274 Limited quantities 5 L E1 Excepted quantities

Packaging

P001, IBC03, LP01, R001 Packing instructions

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T7

TP1, TP28 Special provisions

ADR tank

L4BN Tank code Vehicles for tank carriage ΑT Transport category 3 Tunnel restriction code (E)

Special provision for

packages V12

Railway transport - RID

274 Special provisions Excepted quantities E1

Packaging

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions **MP19**

Portable tanks and bulk containers

Guidelines T7

Special provisions TP1, TP28

RID Tanks

packages

Tank code L4BN Transport category Special provision for W 12

Air transport - ICAO/IATA

Y841 Packaging instructions for limited amount Packaging instructions passenger 852 Cargo packaging instructions 856

Marine transport - IMDG

F-A, S-B EmS (emergency plan) MFAG 320

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Environmental Protection Act 1990 as amended. Clean Air Act 1993 as amended. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

Harmful if swallowed.



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020 Revision date 07th April 2022 2.1 Version

Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation.

H314

H412 Harmful to aquatic life with long lasting effects. Harmful if swallowed or in contact with skin. H302+H312

H302+H332 Harmful if swallowed or if inhaled. Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor CAS Chemical Abstracts Service

Concentration of a substance when it is affected 50% of the population CE₅₀ Regulation (EC) No 1272/2008 on classification, labelling and packaging of CLP

substance and mixtures

DNEL Derived no-effect level

EINECS European Inventory of Existing Commercial Chemical Substances

EL50 Effective Loading for 50% of the tested organisms

EmS Emergency plan

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

IC50 Concentration causing 50% blockade **ICAO** International Civil Aviation Organization **IMDG** International Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients ISO International Organization for Standardization **IUPAC** International Union of Pure and Applied Chemistry

Lethal concentration of a substance in which it can be expected death of 50% of the LC50

population

Lethal dose of a substance in which it can be expected death of 50% of the LD50

population

LL50 Lethal Loading for 50% of tested organisms

log Kow Octanol-water partition coefficient 170 Volatile organic compounds

MARPOL International Convention for the Prevention of Pollution from Ships

NOAEC No observed adverse effect concentration

NOAEL No observed adverse effect level NOEC No observed effect concentration

NOEL No observed effect level



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS EP-400 UV składnik B

Creation date 17th December 2020
Revision date 07th April 2022 Version 2.1

NOELR No Observed Effect Loading Rate
OEL Occupational Exposure Limits
PBT Persistent, Bioaccumulative and Toxic
PNEC Predicted no-effect concentration

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UE European Union

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

vPvB Very Persistent and very Bioaccumulative

WE Identification code for each substance listed in EINECS

Acute Tox. Acute toxicity

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Eye Dam.Serious eye damageEye Irrit.Eye irritationSkin Corr.Skin corrosionSkin Sens.Skin sensitization

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

This safety data sheet replaces version 2.0 of 28/05/2021. Section update: 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.