

according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Nexler EPOLIS WE-200 składnik A

Substance / mixture mixture

UFI KERJ-S0QQ-4002-M5FE

Other mixture names

Nexler EPOLIS WE-200 component A

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Mixture's intended use

Colored, solvent-free, two-component, water-dispersible epoxy composition intended for coating protection of mineral substrates.

#### Main intended use

PC-CON-5 Construction chemicals

### Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

#### 1.3. Details of the supplier of the safety data sheet

#### **Supplier**

Name or trade name NEXLER sp. z o.o.

Address Łużycka 6, Gdynia, 81-537

Poland

Identification number (CRN)191528483VAT Reg NoPL5862073821Phone+48 58 781 45 85E-mailinfo@nexler.comWeb addresswww.nexler.com

#### Competent person responsible for the safety data sheet

Name NEXLER sp. z o.o. E-mail info@nexler.com

# 1.4. Emergency telephone number

National Health Service (NHS) 111

National poisoning information centre Scotland, NHS 24: 111

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318

# Most serious adverse effects on human health and the environment

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage.

### 2.2. Label elements

# Hazard pictogram



#### Signal word

Danger

### **Hazardous substances**

 $3-aminomethyl-3, \\ 5, \\ 5-trimethyl \\ cyclohexylamine$ 

#### **Hazard statements**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

if On Skin (or nair): take oil immediately all contaminated clothing. Rins

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a doctor.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

#### Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

#### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 2086662-49-7 Registration number: - [REACH art. 2 (9)]	Formaldehyde, polymer with N1-(2-aminoethyl)-1,2-ethanediamine, 5-amino-1,3,3-trimethylcyclohexanemethanamine, 2-(chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis][phenol] and poly (ethylene glycol)	5-15	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Index: 612-067-00-9 CAS: 2855-13-2 EC: 220-666-8 Registration number: 01-2119514687-32	3-aminomethyl-3,5,5- trimethylcyclohexylamine	2,5-6	Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Specific concentration limit: ATE Oral = 1030 mg/kg bw Skin Sens. 1A, H317: C ≥ 0.001 %	
CAS: 52470-47-0 Registration number: - [REACH art. 2 (9)]	Formaldehyde, polymer with N-(2-aminoethyl)-1,2-ethanediamine	1-3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
CAS: 129813-66-7 EC: 929-018-5 Registration number: 01-2119475608-26	Hydrocarbons, C10-C13, n-alkanes, <2% aromatics	0,5-1,2	Asp. Tox. 1, H304 EUH066	2
Index: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0 Registration number: 01-2119484609-23	isobutanol	0,1-0,2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	1
CAS: 104-76-7 EC: 203-234-3 Registration number: 01-2119487289-20	2-ethylhexan-1-ol	0,03-0,06	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	1

### **Notes**

- 1 A substance for which exposure limits are set.
- 2 Substance of unknown or variable composition, complex reaction products or biological materials UVCB.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

Full text of all classifications and hazard statements is given in the section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

#### If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Depending on the situation, call the medical rescue service and always ensure medical treatment. Rinse cautiously with water for several minutes. Rinse skin with water or shower.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

#### If swallowed

RINSE THE MOUTH WITH WATER IMMEDIATELY AND LET THE PERSON DRINK 2-5 dl of cold water to reduce the heating effect of the corrosive substance. Consuming larger amounts of liquid is not advisable as it may induce vomiting and potential inhaling of the corrosive substances in the lungs. The affected person must not be forced to drink, particularly if already feeling pain in the mouth or throat. In this case let the affected person only rinse the mouth with water. DO NOT PROVIDE ACTIVATED CARBON! Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible.

### 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

Inhaling vapours can cause corrosion of the breathing system.

#### If on skin

Causes severe skin burns. May cause an allergic skin reaction.

#### If in eyes

Causes serious eye damage.

#### If swallowed

Corrosion of the digestion system can occur.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

### Unsuitable extinguishing media

Water - full jet.

### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

## 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

# 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Storage temperature required between +10 ° C and +25 ° C.

#### 7.3. Specific end use(s)

not available

### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### **United Kingdom**

#### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

	,,		(1 - 11 - 11 - 11 - 1 - 1 - 1 - 1
Substance name (component)		Туре	Value
		WEL 8h	154 mg/m <sup>3</sup>
isobutanal (CAS), 79, 93, 1)		WEL 8h	50 ppm
isobutanol (CAS: 78-83-1)		WEL 15min	231 mg/m <sup>3</sup>
		WEL 15min	75 ppm
2 othylhovan 1 ol (CAS) 104 76 7)		WEL 8h	5,4 mg/m <sup>3</sup>
2-ethylhexan-1-ol (CAS: 104-76-7)		WEL 8h	1 ppm

#### **United Kingdom**

# EH40/2005 Workplace exposure limits (Third edition, published 2018)

Substance name (component)	Туре	Value
	WEL 8h	154 mg/m <sup>3</sup>
isobutanel (CAC), 70, 92, 1)	WEL 8h	50 ppm
isobutanol (CAS: 78-83-1)	WEL 15min	231 mg/m <sup>3</sup>
	WEL 15min	75 ppm



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 2.3 Version

# **DNEL**

2-ethylhexan-1-ol						
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source	
Workers	Dermal	23 mg/kg bw/day	Chronic effects systemic			
Workers	Inhalation	53.2 mg/m <sup>3</sup>	Chronic effects local			
Workers	Inhalation	12.8 mg/m <sup>3</sup>	Chronic effects systemic			
Consumers	Oral	1.1 mg/kg bw/day	Chronic effects systemic			
Consumers	Dermal	11.4 mg/kg bw/day	Chronic effects systemic			
Consumers	Inhalation	2.3 mg/m <sup>3</sup>	Chronic effects systemic			
Consumers	Inhalation	26.6 mg/m <sup>3</sup>	Acute effects local			
Workers	Inhalation	53.2 mg/m³	Acute effects local			
Consumers	Inhalation	26.6 mg/m <sup>3</sup>	Chronic effects local			

3-aminomethyl-3,5,5-trimethylcyclohexylamine					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	0.073 mg/m <sup>3</sup>	Chronic effects local		
Workers	Inhalation	0.073 mg/m <sup>3</sup>	Acute effects local		
Consumers	Oral	0.526 mg/kg bw/day	Chronic effects systemic		

isobutanol						
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source	
Workers	Inhalation	310 mg/m <sup>3</sup>	Chronic effects local			
Consumers	Oral	25 mg/kg bw/day	Chronic effects systemic			
Consumers	Inhalation	55 mg/m <sup>3</sup>	Chronic effects local			

# **PNEC**

2-ethylhexan-1-ol					
Route of exposure	Value	Value determination	Source		
Drinking water	0.017 mg/l				
Marine water	0.0017 mg/l				
Water (intermittent release)	0.17 mg/l				
Freshwater sediment	0.284 mg/kg of dry substance of sediment				
Sea sediments	0.028 mg/kg of dry substance of sediment				
Soil (agricultural)	0.047 mg/kg of dry substance of soil				



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

2-ethylhexan-1-ol				
Route of exposure	Value	Value determination	Source	
Microorganisms in sewage treatment	10 mg/l			
Food chain	55 mg/kg of food			

3-aminomethyl-3,5,5-trin	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
Route of exposure	Value	Value determination	Source			
Drinking water	0.06 mg/l					
Marine water	0.006 mg/l					
Water (intermittent release)	0.23 mg/l					
Microorganisms in sewage treatment	3.18 mg/l					
Freshwater sediment	5.784 mg/kg of dry substance of sediment					
Sea sediments	0.578 mg/kg of dry substance of sediment					
Soil (agricultural)	1.121 mg/kg of dry substance of soil					

isobutanol						
Route of exposure	Value	Value determination	Source			
Drinking water	0.4 mg/l					
Marine water	0.04 mg/l					
Freshwater sediment	1.56 mg/kg of dry substance of sediment					
Sea sediments	0.156 mg/kg of dry substance of sediment					
Soil (agricultural)	0.076 mg/kg of dry substance of soil					
Microorganisms in sewage treatment	10 mg/l					
Water (intermittent release)	11 mg/l					

#### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

Protective goggles.

### Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

vexler

according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

#### **Respiratory protection**

It is not needed.

#### Thermal hazard

Data not available.

#### **Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state liquid

Colour According to the offer

Odour weak
Melting point/freezing point -1 °C

Boiling point or initial boiling point and boiling range 101 °C

Flammability non-inflammable Lower and upper explosion limit not applicable

Flash point not applicable
Auto-ignition temperature not applicable
isobutanol (CAS: 78-83-1) 400 °C

isobutanol (CAS: 78-83-1) 400 °C

Decomposition temperature not applicable
pH 9-10 (10% solution)

Kinematic viscosity

Solubility in water

5-10 (10% solution)

560 mm²/s at 20 °C

miscible with water

Partition coefficient n-octanol/water (log value) does not apply to mixtures Vapour pressure 23.4 hPa (water) at 20 °C

isobutanol (CAS: 78-83-1) 12 hPa at 20 °C

Density and/or relative density

Density 1.39 g/cm³ at 22 °C

Relative vapour density <

Particle characteristics applies to solids

#### 9.2. Other information

not available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts with peroxides, aldehydes, ketones, epoxy resins.

### 10.2. Chemical stability

The product is stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Unknown.

### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

# 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Not developed under normal uses.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

# **Acute toxicity**

Based on the available data, the criteria for classification of the mixture are not met.

2-ethylhexan-1-ol						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD50	OECD 401	2047 mg/kg bw		Rat (Rattus norvegicus)	М
Dermal	LD50	OECD 402	>3000 mg/kg bw	24 hours	Rat (Rattus norvegicus)	F/M
Inhalation	LC50	OECD 403	>0.89 mg/l of air	4 hours	Rat (Rattus norvegicus)	F/M

3-aminomethyl-3	3-aminomethyl-3,5,5-trimethylcyclohexylamine							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex		
Oral	LD50	OECD 401	1030 mg/kg bw		Rat (Rattus norvegicus)	М		
Inhalation (aerosols)	LC50	EPA OPPTS 870.1300	>5.01 mg/l of air	4 hours	Rat (Rattus norvegicus)	F/M		
Dermal	LD50	OECD 402	>2000 mg/kg bw	24 hours	Rat (Rattus norvegicus)	F/M		
Oral	ATE		1030 mg/kg bw					

Hydrocarbons, C:	Hydrocarbons, C10-C13, n-alkanes, <2% aromatics								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex			
Oral	LD50	OECD 401	>15000 mg/kg bw		Rat (Rattus norvegicus)	F/M			
Dermal	LD50	OECD 402	>3160 mg/kg bw		Rabbit	F/M			
Inhalation (vapor)	LC50	OECD 403	>6100 mg/m <sup>3</sup>	4 hours	Rat (Rattus norvegicus)	F/M			

isobutanol	sobutanol								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex			
Oral	LD50	OECD 401	3350 mg/kg bw		Rat (Rattus norvegicus)	F			
Inhalation	LC50		>18.2 mg/l of air	6 hours	Rat (Rattus norvegicus)	F/M			
Dermal	LD50	OECD 402	2000-2460 mg/kg bw	24 hours	Rabbit	F/M			

# Skin corrosion/irritation

Causes severe skin burns and eye damage.

2-ethylhexan-1-ol						
Route of exposure	Result	Method	Exposure time	Species		
Dermal	Highly irritating	OECD 404	4 hours	Rabbit		

3-aminomethyl-3,5,5-trimethylcyclohexylamine						
Route of exposure	Result	Method	Exposure time	Species		
Dermal	Corrosive		24 hours	Rabbit		



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

Method		Exposure time		
		exposure time	9	Species
		nediamine, 5-amin ane, 4,4'-(1-methy		3- idene)bis][phenol] and
Method		Exposure time	9	Species
Method		Exposure time		Species
OECD 4	104	4 hours		Rabbit
	Exposure	time	Specie	es
			Huma	n
	Exposure	time	Specie	es
ge.				
	ge.	ge.	ge.	ge.

_									
Route of exposure	Result	Method	Exposure time	Species					
Eye	Irritating	OECD 405		Rabbit					
3-aminomethyl-3,	3-aminomethyl-3,5,5-trimethylcyclohexylamine								
Route of exposure	Result	Method	Exposure time	Species					
Eye	Corrosive, Serious eye damage	OECD 405		Rabbit					
Formaldehyde, po	lymer with N-(2-amin	oethyl)-1,2-ethan	ediamine						
Route of exposure	Result	Method	Exposure time	Species					
Eye	Irritating								
Formaldehyde, polymer with N1-(2-aminoethyl)-1,2-ethanediamine, 5-amino-1,3,3-trimethylcyclohexanemethanamine, 2-(chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis][phenol] and poly(ethylene glycol)									
Route of exposure	Result	Method	Exposure time	Species					
Eye	Irritating								



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

isobutanol						
Route of exposure	Result	Method	Exposure time	Species		
Eye	Highly irritating, Causes damage	OECD 405	24 hours	Rabbit		

### Respiratory or skin sensitisation

May cause an allergic skin reaction.

3-aminomethyl-3,5,5-trimethylcyclohexylamine							
Route of exposure	Result	Method	Exposure time	Species	Sex		
Dermal	Sensitizing	OECD 406	24 hours	Guinea-pig (Cavia aperea f. porcellus)	М		

### Germ cell mutagenicity

Based on the available data, the criteria for classification of the mixture are not met.

#### Carcinogenicity

Based on the available data, the criteria for classification of the mixture are not met.

#### Reproductive toxicity

Based on the available data, the criteria for classification of the mixture are not met.

### Toxicity for specific target organ - single exposure

Based on the available data, the criteria for classification of the mixture are not met.

### Toxicity for specific target organ - repeated exposure

Based on the available data, the criteria for classification of the mixture are not met.

# Repeated dose toxicity

2-ethylhexan	-1-ol						
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	OECD 408	250 mg/kg bw/day	90 days	Rat (Rattus norvegicus)	F/M
Inhalation	NOAEC	Systemic effects	OECD 413	638.4 mg/m <sup>3</sup>	90 days	Rat (Rattus norvegicus)	F/M

3-aminomethyl-3,5,5-trimethylcyclohexylamine									
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex		
Oral	NOAEL	Systemic effects	OECD 408	59 mg/kg bw/day	13 weeks	Rat (Rattus norvegicus)	F/M		

Hydrocarbons	Hydrocarbons, C10-C13, n-alkanes, <2% aromatics									
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex			
Oral	NOAEL	Systemic effects	OECD 408	≥5000 mg/kg bw/day	90 days	Rat (Rattus norvegicus)	F/M			
Inhalation (vapor)	NOAEC	Systemic effects	OECD 413	≥10400 mg/m³ of air	13 weeks	Rat (Rattus norvegicus)	F/M			



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

isobutanol							
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Inhalation (vapor)	NOAEL	Systemic effects, Effects on fertility		≥7.5 mg/l of air	17 weeks	Rat (Rattus norvegicus)	F/M
Oral	NOAEL	Systemic effects	OECD 408	≥1450 mg/kg bw/day	90 days	Rat (Rattus norvegicus)	F/M

#### **Aspiration hazard**

Based on the available data, the criteria for classification of the mixture are not met.

#### 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

# **Acute toxicity**

2-ethylhexan-1-ol									
Parameter	Method	Value	Exposure time	Species	Environmen t				
LC50	EU C.1 (84/449/EEC)	17.1 mg/l	96 hours	Fish (Leuciscus idus)					
EC50	EU C.2 (84/449/EEC)	39 mg/l	48 hours	Aquatic invertebrates (Daphnia magna)					
EC50		16.6 mg/l	72 hours	Algae (Desmodesmus subspicatus)					

3-aminometh	3-aminomethyl-3,5,5-trimethylcyclohexylamine								
Parameter	Method	Value	Exposure time	Species	Environmen t				
LC50		110 mg/l	96 hours	Fish (Leuciscus idus)					
EC50	OECD 202	23 mg/l	48 hours	Aquatic invertebrates (Daphnia magna)					
ErC50	EU C.3 (87/302/EEC)	>50 mg/l	72 hours	Algae (Desmodesmus subspicatus)					
NOEC		1120 mg/l	18 hours	Aquatic microorganisms (Pseudomonas putida)					
NOEC	EU C.3 (87/302/EEC)	11.2 mg/l	72 hours	Algae (Desmodesmus subspicatus)					

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics									
Parameter	Method	Value	Exposure time	Species	Environmen t				
LL 50	OECD 203	10-30 mg/l	96 hours	Fish (Oncorhynchus mykiss)					
EL 50		>100 mg/l	48 hours	Aquatic invertebrates (Daphnia magna)					



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics								
Parameter	Method	Value	Exposure time	Species	Environmen t			
EL 50	OECD 201	>1000 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)				

isobutanol	sobutanol								
Parameter	Method	Value	Exposure time	Species	Environmen t				
LC50		1430 mg/l	96 hours	Fish (Pimephales promelas)					
EC50		1100 mg/l	48 hours	Aquatic invertebrates (Daphnia pulex)					
EC50	OECD 201	1799 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)					
IC50		>1000 mg/l	16 hours	Aquatic microorganisms	Activated sludge				

# **Chronic toxicity**

3-aminomethyl-3,5,5-trimethylcyclohexylamine									
Parameter	Method	Value	Exposure time	Species	Environmen t				
NOEC	OECD 202	3 mg/l	21 days	Aquatic invertebrates (Daphnia magna)					

# 12.2. Persistence and degradability

The product is not biodegradable to the extent significant for the natural environment.

### **Biodegradability**

2-ethylhexan-1-ol								
Parameter	Method	Value	Exposure time	Environment	Result			
	OECD 301C	79-99.9 %	2 weeks		Easily biodegradable			

3-aminomethyl-3,5,5-trimethylcyclohexylamine								
Parameter	Method	Value	Exposure time	Environment	Result			
		8 %	28 days	Activated sludge	Hardly biodegradable			

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics								
Parameter	Method	Value	Exposure time	Environment	Result			
	OECD 301F	80 %	28 days		Easily biodegradable			

isobutanol								
Parameter	Method	Value	Exposure time	Environment	Result			
ThOD	OECD 301C	90-100 %	14 days		Easily biodegradable			

# 12.3. Bioaccumulative potential

Bioaccumulation is not expected.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

2-ethylhexan-1-ol										
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]				
Log Pow	OECD 117	2.9				25°C				

3-aminomethy	3-aminomethyl-3,5,5-trimethylcyclohexylamine										
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]					
Log Pow	OECD 107	0.99				23°C					

isobutanol	sobutanol					
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	OECD 117	1				25°C

#### 12.4. Mobility in soil

The product is soluble and mobile in water and soil. Contamination of water courses may occur in the event of rain.

3-aminomethyl-3,5,5-tr	-aminomethyl-3,5,5-trimethylcyclohexylamine			
Parameter	Value	Environment	Temperature	
Koc	928		20°C	

#### 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

#### 12.7. Other adverse effects

Data not available.

#### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Danger of environmental contamination, follow the applicable waste disposal regulations. Store unused product and contaminated packaging in closed containers for waste collection and hand over for disposal to a specialized company authorized to conduct such activity. Do not pour unused product into drains. It must not be disposed of together with municipal waste. Empty packaging can be used for energy in a waste incineration plant or collected in a landfill with an appropriate classification. Perfectly cleaned packaging can be recycled. The classification of waste may change depending on where it is generated.

### Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

### **SECTION 14: Transport information**

#### 14.1. UN number or ID number

UN 2735

#### 14.2. UN proper shipping name

AMINES, LIQUID, CORROSIVE, N.O.S. (contains: 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

### 14.3. Transport hazard class(es)

3 Corrosive substances

### 14.4. Packing group

III

# 14.5. Environmental hazards

No.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

#### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### **Additional information**

Hazard identification No.

UN number

Classification code C7

Classification code Safety signs



80

2735

8

### Road transport - ADR

Special provisions 274
Limited quantities 5 L
Excepted quantities E1

**Packaging** 

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T7

Special provisions TP1, TP28

**ADR tank** 

Tank code L4BN
Vehicles for tank carriage AT
Transport category 3
Tunnel restriction code (E)
Special provision for

packages V12

Railway transport - RID

Special provisions 274
Excepted quantities E1

**Packaging** 

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T7

Special provisions TP1, TP28

**RID Tanks** 

Tank code L4BN Transport category 0

Special provision for

packages W12

Air transport - ICAO/IATA

Packaging instructions for limited amount Y841
Packaging instructions passenger 852
Cargo packaging instructions 856

Marine transport - IMDG

EmS (emergency plan) F-A, S-B MFAG 320



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

#### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Clean Air Act 1993 as amended. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Public health act 1961. Environmental Protection Act 1990 as amended. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

#### **SECTION 16: Other information**

# A list of standard risk phrases used in the safety data sheet

П220	riaiiiiiabie iiquid aiid vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

# Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a doctor.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

#### A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

# Key to abbreviations and acronyms used in the safety data sheet

,	,
ADR	uropean agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EC50 Concentration of a substance when it is affected 50% of the population EINECS European Inventory of Existing Commercial Chemical Substances

EL<sub>50</sub> Effective Loading for 50% of the tested organisms

EmS Emergency plan EU European Union



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020
Revision date 10th June 2024 Version 2.3

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

IC50
 ICAO
 International Civil Aviation Organization
 IMDG
 International Maritime Dangerous Goods
 IMO
 International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

LL50 Lethal Loading for 50% of tested organisms

log Kow Octanol-water partition coefficient
NOAEC No observed adverse effect concentration

NOAEL No observed adverse effect level
NOEC No observed effect concentration
OEL Occupational Exposure Limits

PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Acute Tox. Acute toxicity
Asp. Tox. Aspiration hazard
Eye Dam. Serious eye damage
Flam. Liq. Flammable liquid
Skin Corr. Skin corrosion
Skin Sens. Skin sensitization

STOT SE Specific target organ toxicity - single exposure

#### **Training guidelines**

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

# Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

This safety sheet replaces version 2.2 dated 21.09.2022.

Updated sections: 1,8,9,13,15.

#### More information

Classification procedure - calculation method.

#### **Statement**



according to Regulation (EC) No 1907/2006 (REACH) as amended

# Nexler EPOLIS WE-200 składnik A

Creation date 17th December 2020

Revision date 10th June 2024 Version 2.3

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.