

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
Substance / mixture: Nexler EPOLIS WE-300 składnik A
UFI: R4S1-V0TJ-5002-GRQ7
Other mixture names: Nexler EPOLIS WE-300 component A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

A two-component, water-dispersible epoxy composition intended for matting epoxy resin floors and for protecting mineral substrates.

Main intended use

PC-CON-5 Construction chemicals

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name	NEXLER sp. z o.o.
Address	Łużycka 6, Gdynia, 81-537 Poland
Identification number (CRN)	191528483
VAT Reg No	PL5862073821
Phone	+48 58 781 45 85
E-mail	info@nexler.com
Web address	www.nexler.com

Competent person responsible for the safety data sheet

Name	NEXLER sp. z o.o.
E-mail	info@nexler.com

1.4. Emergency telephone number

National Health Service (NHS) 111
National poisoning information centre Scotland, NHS 24: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Skin Corr. 1B, H314

Skin Sens. 1, H317

Eye Dam. 1, H318

Most serious adverse effects on human health and the environment

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage.

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.
P501	Dispose of contents/container to according to the instructions of the manufacturer or person authorized to dispose of waste.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 2086662-49-7 Registration number: - [REACH art. 2 (9)]	Formaldehyde, polymer with N1-(2-aminoethyl)-1,2-ethanediamine, 5-amino-1,3,3-trimethylcyclohexanemethanamine, 2-(chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and poly(ethylene glycol)	5-14	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Index: 612-067-00-9 CAS: 2855-13-2 EC: 220-666-8 Registration number: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine	2,5-5,5	Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Specific concentration limit: ATE Oral = 1030 mg/kg bw Skin Sens. 1A, H317: C ≥ 0.001 %	
CAS: 52470-47-0 Registration number: - [REACH art. 2 (9)]	Formaldehyde, polymer with N-(2-aminoethyl)-1,2-ethanediamine	1-3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	
CAS: 129813-66-7 EC: 929-018-5 Registration number: 01-2119475608-26	Hydrocarbons, C10-C13, n-alkanes, <2% aromatics	0,5-1,2	Asp. Tox. 1, H304 EUH066	2
Index: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0 Registration number: 01-2119484609-23	isobutanol	0,1-0,2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	1
CAS: 104-76-7 EC: 203-234-3 Registration number: 01-2119487289-20	2-ethylhexan-1-ol	0,03-0,06	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	1

Notes

- 1 A substance for which exposure limits are set.
- 2 Substance of unknown or variable composition, complex reaction products or biological materials - UVCB.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Depending on the situation, call the medical rescue service and always ensure medical treatment. Rinse cautiously with water for several minutes. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

RINSE THE MOUTH WITH WATER IMMEDIATELY AND LET THE PERSON DRINK 2-5 dl of cold water to reduce the heating effect of the corrosive substance. Consuming larger amounts of liquid is not advisable as it may induce vomiting and potential inhaling of the corrosive substances in the lungs. The affected person must not be forced to drink, particularly if already feeling pain in the mouth or throat. In this case let the affected person only rinse the mouth with water. DO NOT PROVIDE ACTIVATED CARBON! Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system.

If on skin

Causes severe skin burns. May cause an allergic skin reaction.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date 29th December 2020
Revision date 12th June 2024 Version 2.1

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Storage temperature required between +10 ° C and +25 ° C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

United Kingdom

EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Type	Value
isobutanol (CAS: 78-83-1)	WEL 8h	154 mg/m ³
	WEL 8h	50 ppm
	WEL 15min	231 mg/m ³
	WEL 15min	75 ppm
2-ethylhexan-1-ol (CAS: 104-76-7)	WEL 8h	5,4 mg/m ³
	WEL 8h	1 ppm

United Kingdom

EH40/2005 Workplace exposure limits (Third edition, published 2018)

Substance name (component)	Type	Value
isobutanol (CAS: 78-83-1)	WEL 8h	154 mg/m ³
	WEL 8h	50 ppm
	WEL 15min	231 mg/m ³
	WEL 15min	75 ppm

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

DNEL

2-ethylhexan-1-ol					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	23 mg/kg bw/day	Chronic effects systemic		
Workers	Inhalation	53.2 mg/m ³	Chronic effects local		
Workers	Inhalation	12.8 mg/m ³	Chronic effects systemic		
Consumers	Oral	1.1 mg/kg bw/day	Chronic effects systemic		
Consumers	Dermal	11.4 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	2.3 mg/m ³	Chronic effects systemic		
Consumers	Inhalation	26.6 mg/m ³	Acute effects local		
Workers	Inhalation	53.2 mg/m ³	Acute effects local		
Consumers	Inhalation	26.6 mg/m ³	Chronic effects local		

3-aminomethyl-3,5,5-trimethylcyclohexylamine					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	0.073 mg/m ³	Chronic effects local		
Workers	Inhalation	0.073 mg/m ³	Acute effects local		
Consumers	Oral	0.526 mg/kg bw/day	Chronic effects systemic		

isobutanol					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	310 mg/m ³	Chronic effects local		
Consumers	Oral	25 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	55 mg/m ³	Chronic effects local		

PNEC

2-ethylhexan-1-ol			
Route of exposure	Value	Value determination	Source
Drinking water	0.017 mg/l		
Marine water	0.0017 mg/l		
Water (intermittent release)	0.17 mg/l		
Freshwater sediment	0.284 mg/kg of dry substance of sediment		
Sea sediments	0.028 mg/kg of dry substance of sediment		
Soil (agricultural)	0.047 mg/kg of dry substance of soil		

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date 29th December 2020
Revision date 12th June 2024 Version 2.1

2-ethylhexan-1-ol			
Route of exposure	Value	Value determination	Source
Microorganisms in sewage treatment	10 mg/l		
Food chain	55 mg/kg of food		

3-aminomethyl-3,5,5-trimethylcyclohexylamine			
Route of exposure	Value	Value determination	Source
Drinking water	0.06 mg/l		
Marine water	0.006 mg/l		
Water (intermittent release)	0.23 mg/l		
Microorganisms in sewage treatment	3.18 mg/l		
Freshwater sediment	5.784 mg/kg of dry substance of sediment		
Sea sediments	0.578 mg/kg of dry substance of sediment		
Soil (agricultural)	1.121 mg/kg of dry substance of soil		

isobutanol			
Route of exposure	Value	Value determination	Source
Drinking water	0.4 mg/l		
Marine water	0.04 mg/l		
Freshwater sediment	1.56 mg/kg of dry substance of sediment		
Sea sediments	0.156 mg/kg of dry substance of sediment		
Soil (agricultural)	0.076 mg/kg of dry substance of soil		
Microorganisms in sewage treatment	10 mg/l		
Water (intermittent release)	11 mg/l		

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

Respiratory protection

It is not needed.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	white, grey
Odour	weak
Melting point/freezing point	-1 °C
Boiling point or initial boiling point and boiling range	101 °C
Flammability	non-inflammable
Lower and upper explosion limit	not applicable
Flash point	not applicable
Auto-ignition temperature	not applicable
isobutanol (CAS: 78-83-1)	400 °C
Decomposition temperature	not applicable
pH	9-10 (10% solution)
Kinematic viscosity	60 mm ² /s at 20 °C
Solubility in water	miscible with water
Partition coefficient n-octanol/water (log value)	does not apply to mixtures
Vapour pressure	23.4 hPa (water) at 20 °C
isobutanol (CAS: 78-83-1)	12 hPa at 20 °C
Density and/or relative density	
Density	1.26 g/cm ³ at 22 °C
Relative vapour density	not determined
Particle characteristics	applies to solids

9.2. Other information

not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with peroxides, aldehydes, ketones, epoxy resins.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

2-ethylhexan-1-ol						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD 401	2047 mg/kg bw		Rat (<i>Rattus norvegicus</i>)	M
Dermal	LD ₅₀	OECD 402	>3000 mg/kg bw	24 hours	Rat (<i>Rattus norvegicus</i>)	F/M
Inhalation	LC ₅₀	OECD 403	>0.89 mg/l of air	4 hours	Rat (<i>Rattus norvegicus</i>)	F/M

3-aminomethyl-3,5,5-trimethylcyclohexylamine						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD 401	1030 mg/kg bw		Rat (<i>Rattus norvegicus</i>)	M
Inhalation (aerosols)	LC ₅₀	EPA OPPTS 870.1300	>5.01 mg/l of air	4 hours	Rat (<i>Rattus norvegicus</i>)	F/M
Dermal	LD ₅₀	OECD 402	>2000 mg/kg bw	24 hours	Rat (<i>Rattus norvegicus</i>)	F/M
Oral	ATE		1030 mg/kg bw			

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD 401	>15000 mg/kg bw		Rat (<i>Rattus norvegicus</i>)	F/M
Dermal	LD ₅₀	OECD 402	>3160 mg/kg bw		Rabbit	F/M
Inhalation (vapor)	LC ₅₀	OECD 403	>6100 mg/m ³	4 hours	Rat (<i>Rattus norvegicus</i>)	F/M

isobutanol						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD 401	3350 mg/kg bw		Rat (<i>Rattus norvegicus</i>)	F
Inhalation	LC ₅₀		>18.2 mg/l of air	6 hours	Rat (<i>Rattus norvegicus</i>)	F/M
Dermal	LD ₅₀	OECD 402	2000-2460 mg/kg bw	24 hours	Rabbit	F/M

Skin corrosion/irritation

Causes severe skin burns and eye damage.

2-ethylhexan-1-ol				
Route of exposure	Result	Method	Exposure time	Species
Dermal	Highly irritating	OECD 404	4 hours	Rabbit

3-aminomethyl-3,5,5-trimethylcyclohexylamine				
Route of exposure	Result	Method	Exposure time	Species
Dermal	Corrosive		24 hours	Rabbit

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date 29th December 2020

Revision date 12th June 2024

Version

2.1

Formaldehyde, polymer with N-(2-aminoethyl)-1,2-ethanediamine

Route of exposure	Result	Method	Exposure time	Species
Dermal	Irritating			

Formaldehyde, polymer with N1-(2-aminoethyl)-1,2-ethanediamine, 5-amino-1,3,3-trimethylcyclohexanemethanamine, 2-(chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and poly(ethylene glycol)

Route of exposure	Result	Method	Exposure time	Species
Dermal	Irritating			

isobutanol

Route of exposure	Result	Method	Exposure time	Species
Dermal	Irritating	OECD 404	4 hours	Rabbit

Irritation

2-ethylhexan-1-ol

Route of exposure	Result	Exposure time	Species
Inhalation	Irritating		Human

isobutanol

Route of exposure	Result	Exposure time	Species
Inhalation	Irritating		

Serious eye damage/irritation

Causes severe skin burns and eye damage.

2-ethylhexan-1-ol

Route of exposure	Result	Method	Exposure time	Species
Eye	Irritating	OECD 405		Rabbit

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Result	Method	Exposure time	Species
Eye	Corrosive, Serious eye damage	OECD 405		Rabbit

Formaldehyde, polymer with N-(2-aminoethyl)-1,2-ethanediamine

Route of exposure	Result	Method	Exposure time	Species
Eye	Irritating			

Formaldehyde, polymer with N1-(2-aminoethyl)-1,2-ethanediamine, 5-amino-1,3,3-trimethylcyclohexanemethanamine, 2-(chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and poly(ethylene glycol)

Route of exposure	Result	Method	Exposure time	Species
Eye	Irritating			

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date 29th December 2020
Revision date 12th June 2024 Version 2.1

isobutanol

Route of exposure	Result	Method	Exposure time	Species
Eye	Highly irritating, Causes damage	OECD 405	24 hours	Rabbit

Respiratory or skin sensitisation

May cause an allergic skin reaction.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Result	Method	Exposure time	Species	Sex
Dermal	Sensitizing	OECD 406	24 hours	Guinea-pig (<i>Cavia aperea f. porcellus</i>)	M

Germ cell mutagenicity

Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - repeated exposure

Based on the available data, the criteria for classification of the mixture are not met.

Repeated dose toxicity

2-ethylhexan-1-ol

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	OECD 408	250 mg/kg bw/day	90 days	Rat (<i>Rattus norvegicus</i>)	F/M
Inhalation	NOAEC	Systemic effects	OECD 413	638.4 mg/m ³	90 days	Rat (<i>Rattus norvegicus</i>)	F/M

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	OECD 408	59 mg/kg bw/day	13 weeks	Rat (<i>Rattus norvegicus</i>)	F/M

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	OECD 408	≥5000 mg/kg bw/day	90 days	Rat (<i>Rattus norvegicus</i>)	F/M
Inhalation (vapor)	NOAEC	Systemic effects	OECD 413	≥10400 mg/m ³ of air	13 weeks	Rat (<i>Rattus norvegicus</i>)	F/M

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

isobutanol							
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Inhalation (vapor)	NOAEL	Systemic effects, Effects on fertility		≥7.5 mg/l of air	17 weeks	Rat (<i>Rattus norvegicus</i>)	F/M
Oral	NOAEL	Systemic effects	OECD 408	≥1450 mg/kg bw/day	90 days	Rat (<i>Rattus norvegicus</i>)	F/M

Aspiration hazard

Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Acute toxicity

2-ethylhexan-1-ol					
Parameter	Method	Value	Exposure time	Species	Environment
LC ₅₀	EU C.1 (84/449/EEC)	17.1 mg/l	96 hours	Fish (<i>Leuciscus idus</i>)	
EC ₅₀	EU C.2 (84/449/EEC)	39 mg/l	48 hours	Aquatic invertebrates (<i>Daphnia magna</i>)	
EC ₅₀		16.6 mg/l	72 hours	Algae (<i>Desmodesmus subspicatus</i>)	

3-aminomethyl-3,5,5-trimethylcyclohexylamine					
Parameter	Method	Value	Exposure time	Species	Environment
LC ₅₀		110 mg/l	96 hours	Fish (<i>Leuciscus idus</i>)	
EC ₅₀	OECD 202	23 mg/l	48 hours	Aquatic invertebrates (<i>Daphnia magna</i>)	
ErC ₅₀	EU C.3 (87/302/EEC)	>50 mg/l	72 hours	Algae (<i>Desmodesmus subspicatus</i>)	
NOEC		1120 mg/l	18 hours	Aquatic microorganisms (<i>Pseudomonas putida</i>)	
NOEC	EU C.3 (87/302/EEC)	11.2 mg/l	72 hours	Algae (<i>Desmodesmus subspicatus</i>)	

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics					
Parameter	Method	Value	Exposure time	Species	Environment
LL ₅₀	OECD 203	10-30 mg/l	96 hours	Fish (<i>Oncorhynchus mykiss</i>)	
EL ₅₀		>100 mg/l	48 hours	Aquatic invertebrates (<i>Daphnia magna</i>)	

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

Parameter	Method	Value	Exposure time	Species	Environment
EL ₅₀	OECD 201	>1000 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)	

isobutanol

Parameter	Method	Value	Exposure time	Species	Environment
LC ₅₀		1430 mg/l	96 hours	Fish (Pimephales promelas)	
EC ₅₀		1100 mg/l	48 hours	Aquatic invertebrates (Daphnia pulex)	
EC ₅₀	OECD 201	1799 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)	
IC ₅₀		>1000 mg/l	16 hours	Aquatic microorganisms	Activated sludge

Chronic toxicity

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Exposure time	Species	Environment
NOEC	OECD 202	3 mg/l	21 days	Aquatic invertebrates (Daphnia magna)	

12.2. Persistence and degradability

The product is not biodegradable to the extent significant for the natural environment.

Biodegradability

2-ethylhexan-1-ol

Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301C	79-99.9 %	2 weeks		Easily biodegradable

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Parameter	Method	Value	Exposure time	Environment	Result
		8 %	28 days	Activated sludge	Hardly biodegradable

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301F	80 %	28 days		Easily biodegradable

isobutanol

Parameter	Method	Value	Exposure time	Environment	Result
ThOD	OECD 301C	90-100 %	14 days		Easily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation is not expected.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date 29th December 2020
Revision date 12th June 2024 Version 2.1

2-ethylhexan-1-ol						
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	OECD 117	2.9				25°C

3-aminomethyl-3,5,5-trimethylcyclohexylamine						
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	OECD 107	0.99				23°C

isobutanol						
Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	OECD 117	1				25°C

12.4. Mobility in soil

The product is soluble and mobile in water and soil. Contamination of water courses may occur in the event of rain.

3-aminomethyl-3,5,5-trimethylcyclohexylamine			
Parameter	Value	Environment	Temperature
Koc	928		20°C

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Danger of environmental contamination, follow the applicable waste disposal regulations. Store unused product and contaminated packaging in closed containers for waste collection and hand over for disposal to a specialized company authorized to conduct such activity. Do not pour unused product into drains. It must not be disposed of together with municipal waste. Empty packaging can be used for energy in a waste incineration plant or collected in a landfill with an appropriate classification. Perfectly cleaned packaging can be recycled. The classification of waste may change depending on where it is generated.

Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 2735

14.2. UN proper shipping name

AMINES, LIQUID, CORROSIVE, N.O.S. (contains: 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es)

8 Corrosive substances

14.4. Packing group

III

14.5. Environmental hazards

No.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date 29th December 2020
Revision date 12th June 2024 Version 2.1

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

80

UN number

2735

Classification code

C7

Safety signs

8



Road transport - ADR

Special provisions 274

Limited quantities 5 L

Excepted quantities E1

Packaging

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T7

Special provisions TP1, TP28

ADR tank

Tank code L4BN

Vehicles for tank carriage AT

Transport category 3

Tunnel restriction code (E)

Special provision for

packages V12

Railway transport - RID

Special provisions 274

Excepted quantities E1

Packaging

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T7

Special provisions TP1, TP28

RID Tanks

Tank code L4BN

Transport category 0

Special provision for

packages W12

Air transport - ICAO/IATA

Packaging instructions for limited amount Y841

Packaging instructions passenger 852

Cargo packaging instructions 856

Marine transport - IMDG

EmS (emergency plan) F-A, S-B

MFAG 320

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Clean Air Act 1993 as amended. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Public health act 1961. Environmental Protection Act 1990 as amended. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.
P501	Dispose of contents/container to according to the instructions of the manufacturer or person authorized to dispose of waste.

A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EL ₅₀	Effective Loading for 50% of the tested organisms
EmS	Emergency plan
EU	European Union

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LL ₅₀	Lethal Loading for 50% of tested organisms
log Kow	Octanol-water partition coefficient
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquid
Skin Corr.	Skin corrosion
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

This safety data sheet replaces version 2.0 dated 23.09.2022.

Updated sections: 1,3,8,9,10,13,15.

More information

Classification procedure - calculation method.

Statement

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Nexler EPOLIS WE-300 składnik A

Creation date	29th December 2020	Version	2.1
Revision date	12th June 2024		

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.