

according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier NEXLER PENETRATOR G7

Substance / mixture mixture

UFI 2A3N-G0QR-5007-7066

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Mixture's intended use

Asphalt solution used as a primer for bituminous, solvent-based coating waterproofing and heat-sealable roofing papers. It can be used as a moisture-proof waterproofing for building elements in the ground.

### Main intended use

PC-CON-5 Construction chemicals

### Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

### 1.3. Details of the supplier of the safety data sheet

### Supplier

Name or trade name IZOHAN sp. z o.o.

Address Łużycka 2, Gdynia, 81-963

Poland

Identification number (CRN)191528483VAT Reg NoPL5862073821Phone+48 58 781 45 85E-mailinfo@izohan.euWeb addresswww.izohan.eu

#### Competent person responsible for the safety data sheet

Name IZOHAN sp. z o.o. E-mail info@izohan.eu

### 1.4. Emergency telephone number

National Health Service (NHS) 111

National poisoning information centre Scotland, NHS 24: 111

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

### Most serious adverse physico-chemical effects

Flammable liquid and vapour.

### Most serious adverse effects on human health and the environment

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

### 2.2. Label elements

### **Hazard pictogram**





### Signal word

Warning

#### **Hazardous substances**

reaction mass of ethylbenzene and xylene

#### **Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P264 Wash hands and exposed parts of the body thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

### Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Miytures

# Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 905-588-0 Registration number: 01-2119488216-32	reaction mass of ethylbenzene and xylene	35-40	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	1, 2
CAS: 64742-95-6 EC: 918-668-5 Registration number: 01-2119455851-35	Hydrocarbons, C9, aromatics	5-8	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411 EUH066	1, 3

### **Notes**

1 A substance for which exposure limits are set.



1.1

according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version

- 2 Substance for which biological limit values exist.
- 3 Substance of unknown or variable composition, complex reaction products or biological materials UVCB.

Full text of all classifications and hazard statements is given in the section 16.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

#### If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

### 4.2. Most important symptoms and effects, both acute and delayed

### If inhaled

Cough, headache. May cause respiratory irritation.

#### If on skin

Causes skin irritation.

#### If in eyes

Causes serious eye irritation.

### If swallowed

Irritation, nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

### Unsuitable extinguishing media

Water - full jet.

### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.



1.1

according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021
Revision date 02nd January 2023 Version

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

### 7.3. Specific end use(s)

not available

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

### **United Kingdom**

# EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Туре	Value	Note
ethylbenzene	skin. The assign are those for wh		Can be absorbed through the skin. The assigned substances are those for which there are
ethylberizerie	WEL 8h	100 ppm	concerns that dermal absorption will lead to systemic toxicity.



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

### **United Kingdom**

### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

	1	Value	Note
Substance name (component)	Туре	value	Note
othylhonzono	WEL 15min	552 mg/m³	Can be absorbed through the skin. The assigned substances are those for which there are
ethylbenzene	WEL 15min	125 ppm	concerns that dermal absorption will lead to systemic toxicity.
	WEL 8h	220 mg/m³	
Vulana a m. n. or miyad isamara	WEL 8h	50 ppm	Can be absorbed through the skin. The assigned substances are those for which there are
Xylene, o-,m-,p- or mixed isomers	WEL 15min	441 mg/m³	concerns that dermal absorption will lead to systemic toxicity.
	WEL 15min	100 ppm	
twim athrills and a (CAC, CA7A2, OF, C)	WEL 8h	125 mg/m <sup>3</sup>	
trimethylbenzene (CAS: 64742-95-6)	WEL 8h	25 ppm	

### **Biological limit values**

### **United Kingdom**

# EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Name	Parameter	Value	Tested material	Time of sampling
reaction mass of ethylbenzene and xylene	Methylhippuric acids	650 mmol/mol creatinine	Urine	End of shift

### **DNEL**

Hydrocarbons, C9, aromatics

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	12.5 mg/kg bw/day	Systemic chronic effects		
Workers	Inhalation	151 mg/m <sup>3</sup>	Systemic chronic effects		



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

### Hydrocarbons, C9, aromatics

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Consumers	Dermal	7.5 mg/kg bw/day	Systemic chronic effects		
Consumers	Inhalation	32 mg/m <sup>3</sup>	Systemic chronic effects		
Consumers	Oral	7.5 mg/kg bw/day	Systemic chronic effects		

### reaction mass of ethylbenzene and xylene

Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	442 mg/m <sup>3</sup>	Systemic acute effects		
Workers	Inhalation	442 mg/m <sup>3</sup>	Local acute effects		
Workers	Dermal	212 mg/kg bw/day	Systemic chronic effects		
Workers	Inhalation	221 mg/m <sup>3</sup>	Local chronic effects		
Workers	Inhalation	221 mg/m <sup>3</sup>	Systemic chronic effects		
Consumers	Inhalation	260 mg/m <sup>3</sup>	Systemic acute effects		
Consumers	Inhalation	260 mg/m <sup>3</sup>	Local acute effects		
Consumers	Dermal	125 mg/kg bw/day	Systemic chronic effects		
Consumers	Inhalation	65.3 mg/m <sup>3</sup>	Systemic chronic effects		
Consumers	Inhalation	65.3 mg/m <sup>3</sup>	Local chronic effects		
Consumers	Oral	12.5 mg/kg bw/day	Systemic chronic effects		

### PNEC

reaction mass of ethylbenzene and xylene

Route of exposure	Value	Value determination	Source
Drinking water	0.327 mg/l		
Seawater	0.327 mg/l		
Freshwater sediment	12.46 mg/kg of dry substance of sediment		
Sea sediments	12.46 mg/kg of dry substance of sediment		
Soil (agricultural)	2.31 mg/kg of dry substance of soil		
Water (intermittent release)	0.327 mg/l		
Microorganisms in wastewater treatment plants	6.58 mg/l		

### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

### **Eye/face protection**

Protective goggles.

### Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

#### Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

#### Thermal hazard

Data not available.

### **Environmental exposure controls**

Observe usual measures for protection of the environment, see Section 6.2.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state liquid Colour black

Odour characteristic

Melting point/freezing point <-20 °C

Boiling point or initial boiling point and boiling range ≥136 °C

Flammability flammable liquid and vapor

Lower and upper explosion limit not determined

Flash point 31-40 °C
Auto-ignition temperature not determined
Hydrocarbons, C9, aromatics (CAS: 64742-95-6) >400 °C
reaction mass of ethylbenzene and xylene 432-528 °C

Decomposition temperature not applicable

pH non-soluble (in water) Kinematic viscosity  $>21 \text{ mm}^2/\text{s}$  at 40 °C

Solubility in water insoluble

Solubility in other solvents dissolves in most organic solvents

Partition coefficient n-octanol/water (log value) does not apply to mixtures

Vapour pressure not determined
Hydrocarbons, C9, aromatics (CAS: 64742-95-6) 2 hPa at 20 °C
reaction mass of ethylbenzene and xylene 6,5-9,5 hPa at 20 °C

Density and/or relative density

Density

0,91-0,95 g/cm³ at 22 °C

Relative vapour density >1

Particle characteristics applies to solids

### 9.2. Other information

not available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The mixture is not reactive.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Unknown.

### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Not developed under normal uses.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021

Revision date 02nd January 2023 Version 1.1

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### **Acute toxicity**

Based on available data the classification criteria are not met.

Hydrocarbons, C9, aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Dermal	LD50	OECD 402	>3160 mg/kg bw	24 hour	Rabbit	F/M
Inhalation (vapor)	LC50	OECD 403	>6193 mg/m <sup>3</sup>	4 hour	Rat (Rattus norvegicus)	F/M
Oral	LD50		>3492 mg/kg bw		Rat (Rattus norvegicus)	F/M

### reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD50	EU B.1	3523 mg/kg bw		Rat	М
Inhalation (vapor)	LC50	EU B.2	27124 mg/m <sup>3</sup>	4 hour	Rat	М
Skin	LD50		12126 mg/kg bw		Rabbit	М

### Irritation

reaction mass of ethylbenzene and xylene

Route of exposure	Result	Exposure time	Species
Inhalation	Irritating		

### Skin corrosion/irritation

Causes skin irritation.

Hydrocarbons, C9, aromatics

Route of exposure	Result	Method	Exposure time	Species
Dermal	Slightly irritating	OECD 404		Rabbit

reaction mass of ethylbenzene and xylene

Route of exposure	Result	Method	Exposure time	Species
Dermal	Irritating	EU B.4	4 hour	Rabbit

#### Serious eye damage/irritation

Causes serious eye irritation.

reaction mass of ethylbenzene and xylene

Route of exposure	Result	Exposure time	Species
Eye	Irritating		Rabbit

### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

### Germ cell mutagenicity

Based on available data the classification criteria are not met.

### Carcinogenicity

Based on available data the classification criteria are not met.

### Reproductive toxicity

Based on available data the classification criteria are not met.

### Toxicity for specific target organ - single exposure

May cause respiratory irritation.

### Toxicity for specific target organ - repeated exposure

 $\label{eq:maycause} \mbox{May cause damage to organs through prolonged or repeated exposure.}$ 



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER PENETRATOR G7**

Creation date 17th December 2021

Revision date 02nd January 2023 Version 1.1

#### Repeated dose toxicity

Hydrocarbons, C9, aromatics

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	OECD 408	600 mg/kg bw/day	,	Rat (Rattus norvegicus)	F/M
Inhalation (vapor)	NOAEC	Systemic effects	OECD 452	900 mg/m <sup>3</sup>	1 year	Rat (Rattus norvegicus)	F

reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	EU B.32	250 mg/kg bw/day	103 week	Rat (Rattus norvegicus)	F/M
Inhalation (vapor)	NOAEC	Systemic effects		3515 mg/m <sup>3</sup>	13 week	Dog	М

### **Aspiration hazard**

Based on available data the classification criteria are not met.

### 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

#### **Acute toxicity**

Harmful to aquatic life with long lasting effects.

Hydrocarbons, C9, aromatics

Parameter	Method	Value	Exposure time	Species	Environmen t
ErL 50	OECD 201	2.9 mg/l	72 hour	Algae (Raphidocelis subcapitata)	
EbL 50	OECD 201	2.6 mg/l	72 hour	Algae (Raphidocelis subcapitata)	
EL 50	OECD 202	3.2 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	
LL 50	OECD 203	9.2 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	

reaction mass of ethylbenzene and xylene

Parameter	Method	Value	Exposure time	Species	Environmen t
LC50	OECD 203	2.6 mg/l	96 hour	Fishes (Oncorhynchus mykiss)	
EC50	OECD 201	2.2 mg/l	73 hour	Algae (Pseudokirchneriella subcapitata)	
EC <sub>50</sub>	OECD 209	>157 mg/l	3 hour	Aquatic Activate microorganisms sludge	
NOEC	OECD 201	0.44 mg/l	72 hour	Algae (Pseudokirchneriella subcapitata)	
IC50		220 mg/kg of dry substance of soil	10 hour	Microorganisms	
EC50	OECD 202	1 mg/l	24 hour	Aquatic invertebrates (Daphnia magna)	



according to Regulation (EC) No 1907/2006 (REACH) as amended

# **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

### **Chronic toxicity**

Hydrocarbons, C9, aromatics

Parameter	Method	Value	Exposure time	Species	Environmen t
NOELR		2.14 mg/l	21 day	Aquatic invertebrates (Daphnia magna)	
NOELR		1.23 mg/l	28 day	Fishes (Oncorhynchus mykiss)	
NOEC	OECD 209	>99 mg/l	10 min	Aquatic microorganisms	Activated sludge

reaction mass of ethylbenzene and xylene

Parameter	Method	Value	Exposure time	Species	Environmen t
NOEC		>1.3 mg/l	56 day	Fishes (Salmo gairdneri)	
NOEC		0.96 mg/l	7 day	Aquatic invertebrates (Ceriodaphnia dubia)	
NOEC	OECD 301F	16 mg/l	28 day	Aquatic microorganisms	Activated sludge
NOEC		16 mg/kg of dry substance of soil	14 week	Invertebrates (Eisenia andrei)	

### 12.2. Persistence and degradability

### **Biodegradability**

Hydrocarbons, C9, aromatics

Parameter	Method	Value	Exposure time	Environment	Result	
	OECD 301F	78 %	28 day		Easily biodegradable	
reaction mass of othylhonzone and vylone						

reaction mass of ethylbenzene and xylene

Parameter	Method	Value	Exposure time	Environment	Result
					Easily biodegradable

The product is partially biodegradable.

### 12.3. Bioaccumulative potential

Hydrocarbons, C9, aromatics

Parameter	Value	Exposure time	Species	Environment	Temperature [°C]	Value determinatio n
Log Pow	3.03≤≤4.73					QSAR

reaction mass of ethylbenzene and xylene

Parameter	Value	Exposure time	Species	Environment	Temperature [°C]	Value determinatio n
BCF	25.9					
Log Pow	3.16				20°C	

Bioaccumulation is not expected.

#### Mobility in soil 12.4.

reaction mass of ethylbenzene and xylene

Parameter	Method	Value	Environment	Temperature	
Log Koc	OECD 121	2.73			

The product shows low mobility in soil. The product does not dissolve in water, it stays on the water surface.

### Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

#### 12.6. **Endocrine disrupting properties**



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

#### 12.7. Other adverse effects

Data not available.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Danger of environmental contamination, follow the applicable waste disposal regulations. Store unused product and contaminated packaging in closed containers for waste collection and hand over for disposal to a specialized company authorized to conduct such activity. Do not pour unused product into drains. It must not be disposed of together with municipal waste. Empty packaging can be used for energy in a waste incineration plant or collected in a landfill with an appropriate classification. Perfectly cleaned packaging can be recycled. The classification of waste may change depending on where it is generated.

### Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### **SECTION 14: Transport information**

#### 14.1. UN number or ID number

UN 1993

#### 14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (contains: reaction mass of ethylbenzene and xylene)

#### 14.3. Transport hazard class(es)

3 Flammable liquids

#### 14.4. Packing group

III - substances presenting low danger

### 14.5. Environmental hazards

No.

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

### **Additional information**

Hazard identification No.

**UN** number

Classification code

Safety signs



F1 3





according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021 Revision date 02nd January 2023

Version 1.1

Road transport - ADR

Special provisions 274, 601 Limited quantities 5 L Excepted quantities E1

**Packaging** 

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T4
Special provisions TP1, TP29

**ADR tank** 

Tank codeLGBFVehicles for tank carriageFLTransport category3Tunnel restriction code(D/E)

Special provision for

packages V12 operation S2

Railway transport - RID

Special provisions 274, 601 Excepted quantities E1

**Packaging** 

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T4
Special provisions TP1, TP29

**RID Tanks** 

Tank code LGBF Transport category 0

Special provision for

packages W 12

Marine transport - IMDG

EmS (emergency plan) F-E, S-E MFAG 310

### **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Environmental Protection Act 1990 as amended. Clean Air Act 1993 as amended. Public health act 1961. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

### **SECTION 16: Other information**

### A list of standard risk phrases used in the safety data sheet

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date	17th December 2021		
Revision date	02nd January 2023	Version	1.1

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H312+H332 Harmful in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P264 Wash hands and exposed parts of the body thoroughly after handling.

### A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

#### Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CE<sub>50</sub> Concentration of a substance when it is affected 50% of the population CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

DNEL Derived no-effect level

EINECS European Inventory of Existing Commercial Chemical Substances

EL<sub>50</sub> Effective Loading for 50% of the tested organisms

EmS Emergency plan

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

IC50 Concentration causing 50% blockadeICAO International Civil Aviation OrganizationIMDG International Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

LL<sub>50</sub> Lethal Loading for 50% of tested organisms

log Kow Octanol-water partition coefficient

LZO Volatile organic compounds

MARPOL International Convention for the Prevention of Pollution from Ships

NOAEC No observed adverse effect concentration

NOAEL No observed adverse effect level NOEC No observed effect concentration

NOEL No observed effect level

NOELR No Observed Effect Loading Rate



according to Regulation (EC) No 1907/2006 (REACH) as amended

### **NEXLER PENETRATOR G7**

Creation date 17th December 2021
Revision date 02nd January 2023 Version 1.1

OEL Occupational Exposure Limits

PBT Persistent, Bioaccumulative and Toxic
PNEC Predicted no-effect concentration

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UE European Union

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

vPvB Very Persistent and very Bioaccumulative

WE Identification code for each substance listed in EINECS

Acute Tox. Acute toxicity

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Asp. Tox. Aspiration hazard Eye Irrit. Eye irritation Flam. Liq. Flammable liquid Skin Irrit. Skin irritation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

#### **Training guidelines**

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### **Recommended restrictions of use**

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

This safety data sheet replaces version 1.0 dated 17.12.2021.

Updated sections: 1,2,3,8,9,10,11,12,13,15,16.

#### More information

Classification procedure - calculation method and based on tests of physicochemical properties.

### **Statement**

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.