



## DECLARATION OF PERFORMANCE No. 205-CPR-2023

1. Unique identification code:

Insulating bitumen felt  
**NEXLER Fundament  
(2023/1)**

2. Intended use or uses:

- product for horizontal damp-proof insulation, which is subject to regulations of reaction to fire
- product for horizontal damp-proof insulation,
- products for damp-proof insulation of buildings, underground parts, which are subject to reaction to fire test (Type A),
- products for damp-proof insulation of buildings, underground parts (Type A).

3. The manufacturer:

**NEXLER sp. z o.o.**  
ul. Łużycka 6, 81-537 Gdynia, Poland  
tel., fax +48 58 781 45 85  
e-mail: info@nexler.com

4. Systems of assessment and verification of constancy of performance:

**system 2+ – for the applications: d**  
**system 3 – for the applications: a, b, c**

5. Harmonized standard:

- EN 14967:2006
- EN 13969:2004 and EN 13969:2004/A1:2006

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification (Polskie Centrum Badań i Certyfikacji)

1487 Institute of Ceramics and Building Materials (Instytut Ceramiki i Materiałów Budowlanych)

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Reaction to fire	class E	x, y
Watertightness	≥ 2 kPa (method A)	x, y
Tensile properties: - longitudinal - extension	500 ± 200 N/50 mm (4 ± 2) %	y
- transverse - extension	300 ± 150 N/50 mm (4 ± 2) %	
Resistance to static loading	NPD	y
Resistance to impact	NPD	x, y
Tear resistance: - longitudinal - transverse	100 ± 60 N 100 ± 60 N	y
Joint strength: shear: - longitudinal - transverse	300 ± 150 N/50 mm 500 ± 200 N/50 mm	y
Durability: - durability after artificial ageing/degradation, watertightness - chemical resistance	≥ 2 kPa (method A) acc. annex A of standard	x, y
Flexibility at low temperature	≤ 0°C	x, y
Dangerous substances	NPD	x, y

The performances of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Konrad Liberda

Kierownik Grupy Produktowej  
Współpraca Techniczna  
Konrad Liberda

Edition 2, Gdynia, 12.01.2024

