



## DECLARATION OF PERFORMANCE No. 188-CPR-2024

1. Unique identification code:

Heat-weldable underlayer bitumen membrane

### NEXLER PREMIUM PYE PV200 S40 (2024/2)

2. Intended use or uses:

- waterproofing of roofs, which is the subject to fire reaction test,
- waterproofing of roofs,
- products for damp-proof insulation of buildings, including products for waterproofing of underground parts, which are the subject to fire reaction test (Type A and T),
- products for damp-proof insulation of buildings, including products for waterproofing of underground parts (Type A and T).
- products for regulating water vapor permeation, which are the subject to regulations of reaction to fire,
- products for regulating water vapor permeation

3. The manufacturer:

**NEXLER Sp. z o.o.**  
**ul. Łużycka 6, 81-537 Gdynia, Polska**  
**tel., fax +48 58 781 45 85**  
**e-mail: info@nexler.com**

4. Systems of assessment and verification of constancy of performance:

**system 2+ – for the applications: b, d**  
**system 3 – for the applications: a, c, e, f.**

5. Harmonized standard:

- EN 13707:2004+A2:2009
- EN 13969:2004 and EN 13969:2004/A1:2006
- EN 13970:2004 and EN 13970:2004/A1:2006

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification  
(Polskie Centrum Badań i Certyfikacji)

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Resistance to external fire exposure	NPD	x
Reaction to fire	class E	x, y, z
Watertightness	≥ 2 kPa (method A)	z
	≥ 10 kPa (method A)	x
	≥ 60 kPa (method A)	y
Maximum tensile force: - longitudinal - extension	900 ± 300 N/50 mm (50 ± 15) %	x, y, z
	- transverse - extension	
Resistance to root penetration	NPD	x
Resistance to static loading	≥ 15 kg (method B)	x, y
Resistance to impact	ND	x
	≥ 800 mm (method A)	y, z
Tear resistance: -longitudinal -transverse	300 ± 100 N	x, y, z
	300 ± 100 N	
Joint strength: - peel  - shear:  - longitudinal - transverse	NPD	x
	NPD	x
	650 ± 300 N/50 mm 850 ± 300 N/50 mm	y, z
Durability  - durability after artificial ageing, watertightness  - durability against chemical  -after artificial ageing,vapour diffusion  - chemicals resistance	NPD	x
	≥ 60 kPa (method A)	y
	acc. annex A of standard	
	7,5E+11 m <sup>2</sup> *Pa*s/kg ± 50%	z
	acc. Annex A of standard	
Flexibility	≤ -25°C	x
Flexibility in low temperature	≤ -25°C	y, z
Permeation of water vapor	7,5E+11 m <sup>2</sup> *Pa*s/kg ± 25%	z
Dangerous substances	NPD	x, y, z

The performances of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Konrad Liberda

  
Kierownik Biura Produkcyjnej  
i Wspierającej Technicznej  
Konrad Liberda

Gdynia, 29.04.2024

