

DECLARATION OF PERFORMANCE
No. 664-CPR-2023

1. Unique identification of the product-type:

NEXLER Masa Zalewowa na Gorąco typ N2 01

2. Intended use/es:

Joints in roads, airfields, bridge decks, parking decks etc.

3. Manufacturer:

NEXLER sp. z o.o.

ul. Łużycka 6, 81-537 Gdynia, Polska

tel., fax +48 58 781 45 85

www.nexler.com

4. System/s of AVCP:

System 4

5. Harmonised standard:

EN 14188-1:2004

Notified body/ies:

Not applicable

6. Declared performance/es:

Essential characteristics	Performance of the product
Bonding strength	NPD
Cohesion	NPD
Watertightness	NPD
Resistance to deformation <ul style="list-style-type: none"> • Penetration and recovery (resilience) at +25 °C, 75 g ball, 5 s, in % • Cone penetration at +25 °C, 5 s, 150 g, in 0,1 mm • Heat stability/change in penetration value at +70 °C/168 h: <ul style="list-style-type: none"> -cone penetration, in 0,1 mm -penetration and recovery (resilience), in % • Flow resistance, initial and heat degradation at +60 °C, 5 h, 75° angle, in mm 	≤60 40-100 40-100 ≤60 ≤3
Durability of cohesion against liquid chemicals	NPD
Durability of bonding strength and watertightness in the contact with asphalt pavements	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Dawid Dębski at Gdynia on 27.11.2023. (2nd issue)

dyrektor ds. badań

 dr inż. Dawid Dębski