

**NATIONAL DECLARATION OF PERFORMANCE
No. 688-KDWU-2022**

1. *Name and trade name of the construction product:*
 Name: NEXLER Klej do Pap i Gontów cold asphalt binder PN-B-24620
 Trade name: NEXLER Klej do Pap i Gontów

2. *Identification of the type of the construction product:*

NEXLER Klej do Pap i Gontów 01

3. *Intended use or uses:*

Cold asphalt binder NEXLER Klej do Pap i Gontów is primarily used to bond bitumen waterproofing membranes to concrete substrates, to bond waterproofing membranes in multilayer waterproofing systems.

4. *Name and address of the manufacturer:*

NEXLER sp. z o.o.
 ul. Łużycka 6, 81-537 Gdynia, Poland
 tel., fax +48 58 781 45 85
 www.nexler.com

Production site:
 Poland

5. *Name and address of authorised representative, where applicable:*
 not applicable

6. *National system applied for assessment and verification of constancy of performance:*

3

7. *National technical specification:*

7a. *Polish product standard:* PN-B-24620:1998 Cold asphalt binders, compounds and solutions, PN-B-24620:1998/Az1:2004

Name of accredited certification body, number of accreditation and number of national certificate or name of accredited laboratory/laboratories and number of accreditation: Polskie Centrum Badań i Certyfikacji S.A., Oddział Badań i Certyfikacji w Gdańsku, Laboratorium Wyrobów Budowlanych, AB 011

7b. *National Technical Assessment:* not applicable

Technical Assessment Body/ National Technical Assessment Body: not applicable

Name of accredited certification body, number of accreditation and number of certificate: not applicable

8. *Declared performance:*


<i>Essential characteristics of construction product for the intended use or uses</i>	<i>Declared performance</i>	<i>Remarks</i>
Flowability at temperature (60 ± 2) °C and inclination of 45° after 5 h - roofing felt bonded with asphalt binder	unacceptable displacement of the roofing felt and leakage of the binder	
Flexibility when bending on a roller with a diameter of 30 mm at temperature -5 °C	no scratches or cracks	
Pensky-Martens flash point, °C, no less than	> 40	
Water content, % (m/m), no more than	0,5	
Adhesive strength of the roofing felt to roofing felt, N, no less than	150	

9. *The performance of the product identified above is in conformity with all declared performance in clause 8. This national declaration of performance is issued in accordance with the act on construction products dated 16 April 2004 under the sole responsibility of the manufacturer.*

Signed for and on behalf of the manufacturer by:

Dawid Dębski, R&D Manager
 (name and function)

Gdynia, 04.12.2023, issue 2
 (place and date of issue)

dyrektor ds. badań

 dr inż. Dawid Dębski
 (signature)