

according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier NEXLER EPOLIS EP 602 składnik B

Substance / mixture mixture

UFI 3NWJ-N0TW-T008-Y00C

Other mixture names

NEXLER EPOLIS EP 602 pion/poziom składnik B NEXLER EPOLIS EP 602 rozlewna składnik B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

A two-component, flexible epoxy membrane that protects mineral substrates against water, sewage, and chemically aggressive substances, and in the version with sand, an abrasion-resistant surface-insulation for indoor and outdoor use.

Main intended use

PC-CON-5 Construction chemicals

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name IZOHAN sp. z o.o.

Address Łużycka 2, Gdynia, 81-963

Poland

Identification number (CRN)191528483VAT Reg NoPL5862073821Phone+48 58 781 45 85E-mailinfo@izohan.euWeb addresswww.izohan.eu

Competent person responsible for the safety data sheet

Name IZOHAN sp. z o.o. E-mail info@izohan.eu

1.4. Emergency telephone number

National Health Service (NHS) 111

National poisoning information centre Scotland, NHS 24: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Acute Tox. 4, H302 Skin Corr. 1A, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse effects on human health and the environment

Causes serious eye damage. May cause an allergic skin reaction. Causes severe skin burns and eye damage. Harmful if swallowed. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

vexler

according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

Polyoxypropylenediamine Phenol, styrenated

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a doctor.

P391 Collect spillage.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

	· · · · y · · · · ·						
Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note			
CAS: 9046-10-0 Registration number: - [REACH art. 2 (9)]	Polyoxypropylenediamine	30-<50	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412				
CAS: 61788-44-1 EC: 262-975-0 Registration number: 01-2119979575-18	Phenol, styrenated	25-<30	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	1			



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 25513-64-8 EC: 247-063-2 Registration number: 01-2119560598-25	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	5-<10	Acute Tox. 4, H302 Skin Corr. 1A, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318	
CAS: 2156592-58-2 EC: 701-068-0 Registration number: 01-2119473798-17	Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl	5-<10	Acute Tox. 4, H302 Asp. Tox. 1, H304 Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 (ingestion) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	1
Index: 603-069-00-0 CAS: 90-72-2 EC: 202-013-9 Registration number: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol	3-<5	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318	

Notes

1 Substance of unknown or variable composition, complex reaction products or biological materials - UVCB.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Depending on the situation, call the medical rescue service and always ensure medical treatment. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Rinse skin with water or shower. Rinse cautiously with water for several minutes.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

RINSE THE MOUTH WITH WATER IMMEDIATELY AND LET THE PERSON DRINK 2-5 dl of cold water to reduce the heating effect of the corrosive substance. Consuming larger amounts of liquid is not advisable as it may induce vomiting and potential inhaling of the corrosive substances in the lungs. The affected person must not be forced to drink, particularly if already feeling pain in the mouth or throat. In this case let the affected person only rinse the mouth with water. DO NOT PROVIDE ACTIVATED CARBON! Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible.

nexler

according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system.

If on skin

Causes severe skin burns. May cause an allergic skin reaction.

If in eves

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage. As a result of thermal decomposition or reactions with incompatible substances, compounds such as nitric acid, ammonia, nitrogen oxides, aldehydes may be formed. Nitrogen oxides can react with water vapor to form caustic nitric acid.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up.

7.3. Specific end use(s)

not available



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains no substances for which occupational exposure limits are set.

7.4 mg/m³

2.1 mg/kg

bw/day 1.31

mg/m³ 0.75 mg/kg

bw/day 0.75 mg/kg

bw/day

Inhalation

Inhalation

Dermal

Dermal

Oral

DNEL

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Workers /	Route of	Value	Effect	Value	Source
consumers Consumers	exposure Oral	0.05 mg/kg	Systemic chronic effects	determination	
Consumers	Orai	bw/day	Systemic chronic enects		
2,4,6-tris(dime	thylaminomethyl)phenol		.	•
Workers /	Route of	Value	Effect	Value	Source
consumers	exposure			determination	Source
Workers	Inhalation	0.53 mg/m ³	Systemic chronic effects		
Workers	Inhalation	2.1 mg/m ³	Systemic acute effects		
Workers	Dermal	0.15 mg/kg bw/day	Systemic chronic effects		
Workers	Dermal	0.6 mg/kg bw/day	Systemic acute effects		
Consumers	Inhalation	0.13 mg/m ³	Systemic chronic effects		
Consumers	Inhalation	0.13 mg/m ³	Systemic acute effects		
Consumers	Dermal	0.075 mg/kg bw/day	Systemic chronic effects		
Consumers	Dermal	0.075 mg/kg bw/day	Systemic acute effects		
Consumers	Oral	0.075 mg/kg bw/day	Systemic chronic effects		
Amines, C12-1	8-(even numbere	d) and C18-(u	nsaturated) alkyl	•	•
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Consumers	Oral	0.04 mg/kg bw/day	Systemic chronic effects		
Workers	Inhalation	0.38 mg/m ³	Systemic chronic effects		
Workers	Inhalation	1 mg/m³	Local chronic effects		
Workers	Inhalation	1 mg/m ³	Local acute effects		
Consumers	Inhalation	0.035 mg/m ³	Systemic chronic effects		
Phenol, styrena	ited				
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
14/	To be a least a	7 4 / 2	Construction also and a sett		

Systemic chronic effects

Workers

Workers

Consumers

Consumers

Consumers



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

PNEC

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2/2/ (of 2/1/) difficulty mediante 2/0 didmine					
Value	Value determination	Source			
0.102 mg/l					
0.315 mg/l					
0.01 mg/l					
72 mg/l					
0.622 mg/kg of dry substance of sediment					
0.062 mg/kg of dry substance of sediment					
10 mg/kg of dry substance of soil					
	0.102 mg/l 0.315 mg/l 0.01 mg/l 72 mg/l 0.622 mg/kg of dry substance of sediment 0.062 mg/kg of dry substance of sediment 10 mg/kg of dry	0.102 mg/l 0.315 mg/l 0.01 mg/l 72 mg/l 0.622 mg/kg of dry substance of sediment 0.062 mg/kg of dry substance of sediment 10 mg/kg of dry			

2,4,6-tris(dimethylaminomethyl)phenol

Route of exposure	Value	Value determination	Source
Drinking water	0.046 mg/l		
Seawater	0.005 mg/l		
Water (intermittent release)	0.46 mg/l		
Microorganisms in wastewater treatment plants	0.2 mg/l		
Freshwater sediment	0.262 mg/kg of dry substance of sediment		
Sea sediments	0.026 mg/kg of dry substance of sediment		
Soil (agricultural)	0.025 mg/kg of dry substance of soil		

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Route of exposure	Value	Value determination	Source
Drinking water	0.26 μg/l		
Seawater	0.026 μg/l		
Microorganisms in wastewater treatment plants	550 μg/l		
Freshwater sediment	3.76 mg/kg of dry substance of sediment		
Sea sediments	0.376 mg/kg of dry substance of sediment		
Soil (agricultural)	10 mg/kg of dry substance of soil		
Water (intermittent release)	1.6 µg/l		

Phenol, styrenated

Route of exposure	Value	Value determination	Source
Drinking water	4 μg/l		
Water (intermittent release)	46 μg/l		



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Phenol, styrenated

Route of exposure	Value	Value determination	Source
Seawater	0.4 μg/l		
Microorganisms in wastewater treatment plants	36.2 mg/l		
Freshwater sediment	0.248 mg/kg of dry substance of sediment		
Sea sediments	0.0248 mg/kg of dry substance of sediment		
Soil (agricultural)	0.0473 mg/kg of dry substance of sediment		

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Colour straw colored
Odour amine

Melting point/freezing point <-20 °C
Boiling point or initial boiling point and boiling range >120 °C

Flammability The product is non-flammable.

Lower and upper explosion limit not applicable
Flash point >100 °C
Auto-ignition temperature not determined

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl (CAS: 2156592-58-2) 255 °C Decomposition temperature >120 °C

Solubility in water partially soluble

Partition coefficient n-octanol/water (log value) does not apply to mixtures

Vapour pressure not determined 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine (CAS: 0,04 hPa at 20 °C

25513-64-8)

Density and/or relative density

Density 0,99 g/cm³ at 22 °C



norvegicus)

according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Relative vapour density Particle characteristics >1 applies to solids

9.2. Other information

not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with peroxides, aldehydes, ketones, epoxy resins.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Reactive metals (e.g. sodium, calcium, zinc, etc.). Substances which react with hydroxyl compounds. Mineral Acids. Organic acids (i.e. acetic acid, citric acid etc.). Sodium hypochlorite. Oxidizing agents, reaction with peroxides may cause rapid decomposition of the peroxide with the possibility of an explosion.

10.6. Hazardous decomposition products

Not developed under normal uses. As a result of thermal decomposition or reactions with incompatible substances, compounds such as nitric acid, ammonia, nitrogen oxides, carbon oxides, aldehydes may be formed. Nitrogen oxides can react with water vapor to form caustic nitric acid.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Harmful if swallowed.

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD50		910 mg/kg bw		Rat (Rattus norvegicus)	М
2,4,6-tris(dimethyl	aminomethyl)p	henol				
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Dermal	LD50		>1 ml/kg bw	6 hour	Rat (Rattus norvegicus)	М
Oral	LD50	OECD 401	2169 mg/kg bw		Rat (Rattus norvegicus)	F/M
Amines, C12-18-(e	ven numbered)	and C18-(unsatu	rated) alkyl			
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Dermal	LD50	OECD 402	>2000 mg/kg bw		Rat (Rattus norvegicus)	F/M
Oral	LD50	OECD 401	1300 mg/kg bw		Rat (Rattus norvegicus)	F/M
Phenol, styrenated						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Dermal	LD50	OECD 402	>2000 mg/kg bw	24 hour	Rat (Rattus norvegicus)	F/M
Oral	LD ₅₀	OECD 423	>2000 mg/kg bw		Rat (Rattus	F



Rabbit

Species

according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Polyoxypropylenediamine

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Dermal	LD50		2085.8 mg/kg bw		Rabbit	
Inhalation (vapor)	LC50	OECD 403	>0.74 mg/l	8 hour	Rat (Rattus norvegicus)	F/M

Irritation

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Route of exposure	Result	Exposure time	Species
Inhalation	Irritating		

Skin corrosion/irritation

Causes severe skin burns and eye damage.

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Route of exposure	Result	Method	Exposure time	Species		
Dermal	Corrosive	OECD 404		Rabbit		
2,4,6-tris(dimethylaminomethyl)phenol						
Route of exposure	Result	Method	Exposure time	Species		
Dermal	Corrosive	OECD 435				
Amines, C12-18-(ev	en numbered) and C18-	(unsaturated) alkyl				
Route of exposure	Result	Method	Exposure time	Species		
Dermal	Corrosive	OECD 404	1 hour	Rabbit		
Polyoxypropylenediamine						
Route of exposure	Result	Method	Exposure time	Species		

1 hour

Exposure time

OECD 404

Method

Serious eye damage/irritation

Dermal

Route of exposure

Causes serious eye damage. Causes severe skin burns and eye damage.

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Result

Corrosive

Eye	Corrosive	OECD 405		Rabbit			
2,4,6-tris(dimethyla	2,4,6-tris(dimethylaminomethyl)phenol						
Route of exposure	Result	Method	Exposure time	Species			
Eye	Corrosive						
Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl							

Route of exposure Res	sult	Method	Exposure time	Species
Eye Hig	ghly irritating	OECD 405	24 hour	Rabbit

Polyoxypropylenediamine

Route of exposure	Result	Method	Exposure time	Species
Serious eye damage				Rabbit

Respiratory or skin sensitisation

May cause an allergic skin reaction.

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Route of exposure	Result	Method	Exposure time	Species	Sex
Dermal	Sensitizing	OECD 406		Guinea-pig (Cavia aperea f. porcellus)	F



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Phenol, styrenated

Route of exposure	Result	Method	Exposure time	Species	Sex
Dermal	Sensitizing	OECD 429		Mouse	

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Repeated dose toxicity

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

2,2,1(01 2,1,1)	, crimecity inexa	ne 1,0 diamini	<u> </u>				
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	LOAEL			60 mg/kg bw/day	13 week	Rat (Rattus norvegicus)	F/M
Oral	NOAEL			10 mg/kg bw/day	13 week	Rat (Rattus norvegicus)	F/M
2,4,6-tris(dimethylaminomethyl)phenol							
Danta of							

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	OECD 422	15 mg/kg bw/day	54 day	Rat (Rattus norvegicus)	F/M

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	OECD 407	3.25 mg/kg bw/day	29 day	Rat (Rattus norvegicus)	F/M

Phenol, styrenated

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects		150 mg/kg bw/day	36 week	Rat (Rattus norvegicus)	F/M

Polyoxypropylenediamine

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
	NOAEL		OECD 411	250 mg/kg bw		Rat (Rattus norvegicus)	F/M

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Acute toxicity

Very toxic to aquatic life with long lasting effects. 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Parameter	Method	Value	Exposure time	Species	Environmen t
LC50		174 mg/l	48 hour	Fishes (Leuciscus idus)	
EC50		31.5 mg/l	24 hour	Aquatic invertebrates (Daphnia magna)	
ErC50	OECD 201	43.5 mg/l	72 hour	Algae (Selenastrum capricornutum)	
LOEC	OECD 201	40 mg/l	72 hour	Algae (Selenastrum capricornutum)	
NOEC	OECD 201	16 mg/l	72 hour	Algae (Selenastrum capricornutum)	
EC50		89 mg/l	17 hour	Aquatic microorganisms (Pseudomonas putida)	
NOEC	OECD 216	1000 mg/kg of dry substance of soil	28 day	Microorganisms	Activated sludge

2,4,6-tris(dimethylaminomethyl)phenol

Parameter	Method	Value	Exposure time	Species	Environmen t
LC50		175 mg/l	96 hour	Fishes (Cyprinus carpio)	
EC50		718 mg/l	96 hour	Aquatic invertebrates (Palaeomonetes vulgaris)	
ErC50	OECD 201	46.7 mg/l	72 hour	Algae (Selenastrum capricornutum)	
NOEC	OECD 201	25.1 mg/l	72 hour	Algae (Selenastrum capricornutum)	

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Parameter	Method	Value	Exposure time	Species	Environmen t
LC50	OECD 203	0.84 mg/l	96 hour	Fishes (Danio rerio)	
EC50	OECD 202	0.32 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	
EbC50	OECD 201	0.08 mg/l	72 hour	Algae (Selenastrum capricornutum)	
ErC50	OECD 201	0.16 mg/l	72 hour	Algae (Selenastrum capricornutum)	
EC50	OECD 209	14 mg/l	3 hour	Aquatic microorganisms	Activated sludge
LC50	OECD 207	>1000 mg/kg of dry substance of soil	14 day	Invertebrates (Eisenia fetida)	

Phenol, styrenated

Parameter	Method	Value	Exposure time	Species	Environmen t
LC50		5.6 mg/l	96 hour	Fishes (Danio rerio)	
EL 50	OECD 201	20.42 mg/l	72 hour	Algae (Selenastrum capricornutum)	
EC50		362 mg/l	3 hour	Aquatic microorganisms	Activated sludge



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Phenol, styrenated

Parameter	Method	Value	Exposure time	Species	Environmen t
EC50	OECD 202	4.6 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	

Polyoxypropylenediamine

Parameter	Method	Value	Exposure time	Species	Environmen t
LC50		600 mg/l	96 hour	Fishes (Cyprinodon variegatus)	
EC50	OECD 202	80 mg/l	48 hour	Aquatic invertebrates (Daphnia magna)	
EC50	OECD 201	15 mg/l	72 hour	Algae (Selenastrum capricornutum)	
EC50	OECD 209	750 mg/l		Aquatic microorganisms	Activated sludge

Chronic toxicity

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Parameter	Method	Value	Exposure time	Species	Environmen t
NOEC	OECD 210	≥10.9 mg/l	30 day	Fishes (Danio rerio)	
NOEC	OECD 211	1.02 mg/l	21 day	Aquatic invertebrates (Daphnia magna)	
NOEC	OECD 222	≥1000 mg/kg of dry substance of soil	56 day	Invertebrates (Eisenia fetida)	-

2,4,6-tris(dimethylaminomethyl)phenol

Parameter	Method	Value	Exposure time	Species	Environmen t
NOEC		2 mg/l	28 day	Aquatic microorganisms	Activated sludge

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Parameter	Method	Value	Exposure time	Species	Environmen t
NOEC	OECD 222	200 mg/kg of dry substance of soil	8 week	Invertebrates (Eisenia fetida)	
NOEC	OECD 211	0.013 mg/l	21 day	Aquatic invertebrates (Daphnia magna)	

Phenol, styrenated

Parameter	Method	Value	Exposure time	Species	Environmen t
NOEC	OECD 210	0.2 mg/l	96 hour	Fishes (Danio rerio)	
NOEC		0.2 mg/l	21 day	Aquatic invertebrates (Daphnia magna)	

12.2. Persistence and degradability

Biodegradability

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Parameter	Method	Value	Exposure time	Environment	Result
		7 %	28 day	Activated sludge	Hardly biodegradable
2 4 6 401-(-110		- I			

2,4,6-tris(dimethylaminomethyl)phenol

Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301D	4 %	· · · /	Activated sludge	Hardly biodegradable



Value determination

according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date Revision date

13th February 2023

1.0 Version

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301B	62 %	29 day	Activated sludge	Easily biodegradable

Phenol, styrenated

Parameter	Method	Value	Exposure time	Environment	Result
	OECD 310	4 %	28 day		Hardly biodegradable

The product is partially biodegradable.

12.3. **Bioaccumulative potential**

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	OECD 117	-0.3				25°C

2,4,6-tris(dimethylaminomethyl)phenol

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow		-0.66				21,5°C

Amines, C12-18-(even numbered) and C18-(unsaturated) alkyl

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
BCF		173		Fishes		
Log Pow		4.33				25°C

Phenol, styrenated

Parameter	Method	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	OECD 117	3.03				23,6°C

Bioaccumulation is not expected.

12.4. Mobility in soil

Parameter

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

Value

Koc	25		20°C	QSAR
Phenol, styrenated				
Parameter	Value	Environment	Temperature	Value determination
Koc	584.7		25°C	

Environment

Temperature

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

The product is soluble and mobile in water and soil. Contamination of water courses may occur in the event of rain.



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

13.1. Waste treatment methods

Danger of environmental contamination, follow the applicable waste disposal regulations. Store unused product and contaminated packaging in closed containers for waste collection and hand over for disposal to a specialized company authorized to conduct such activity. Do not pour unused product into drains. It must not be disposed of together with municipal waste. Empty packaging can be used for energy in a waste incineration plant or collected in a landfill with an appropriate classification. Perfectly cleaned packaging can be recycled. The classification of waste may change depending on where it is generated.

Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 2735

14.2. UN proper shipping name

AMINES, LIQUID, CORROSIVE, N.O.S. (contains: polyoxypropylenediamine)

14.3. Transport hazard class(es)

8 Corrosive substances

14.4. Packing group

II - substances presenting medium danger

14.5. Environmental hazards

Yes.

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code

Safety signs

80 2735

С7

8+hazardous for the environment





Road transport - ADR

Special provisions 274
Limited quantities 1 L
Excepted quantities E2

Packaging

Packing instructions P001, IBC02
Mixed packing provisions MP15

Portable tanks and bulk containers

Guidelines T11
Special provisions TP1, TP27

ADR tank

Tank codeL4BNVehicles for tank carriageATTransport category2Tunnel restriction code(E)



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Railway transport - RID

Special provisions 274
Excepted quantities E2

Packaging

Packing instructions P001, IBC02

Mixed packing provisions MP15

Portable tanks and bulk containers

Guidelines T11
Special provisions TP1, TP27

RID Tanks

Tank code L4BN Transport category 0

Air transport - ICAO/IATA

Packaging instructions for limited amount Y840
Packaging instructions passenger 851
Cargo packaging instructions 855

Marine transport - IMDG

EmS (emergency plan) F-A, S-B MFAG 320

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Environmental Protection Act 1990 as amended. Clean Air Act 1993 as amended. Public health act 1961. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet H302 Harmful if swallowed.

11302	Harring in Swanowea.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a doctor.

P391 Collect spillage.

P501 Dispose of contents/container to according to the instructions of the manufacturer

or person authorized to dispose of waste.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CE₅₀ Concentration of a substance when it is affected 50% of the population CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

DNEL Derived no-effect level

EINECS European Inventory of Existing Commercial Chemical Substances

EL₅₀ Effective Loading for 50% of the tested organisms

EmS Emergency plan

EuPCS European Product Categorisation System
IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

LD50 Lethal dose of a substance in which it can be expected death of 50% of the

population

LOAEL Lowest observed adverse effect level log Kow Octanol-water partition coefficient

LZO Volatile organic compounds

MARPOL International Convention for the Prevention of Pollution from Ships

NOAELNo observed adverse effect levelNOECNo observed effect concentrationOELOccupational Exposure Limits

PBT Persistent, Bioaccumulative and Toxic
PNEC Predicted no-effect concentration

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UE European Union

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

vPvB Very Persistent and very Bioaccumulative

WE Identification code for each substance listed in EINECS

Acute Tox. Acute toxicity

Aquatic Acute Hazardous to the aquatic environment

Aquatic Chronic Hazardous to the aquatic environment (chronic)



according to Regulation (EC) No 1907/2006 (REACH) as amended

NEXLER EPOLIS EP 602 składnik B

Creation date 13th February 2023

Revision date Version 1.0

Asp. Tox. Aspiration hazard
Eye Dam. Serious eye damage
Skin Corr. Skin corrosion
Skin Irrit. Skin irritation
Skin Sens. Skin sensitization

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.