

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date	22nd February 2023	Version	1.1
Revision date	21st April 2023		

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier** BRIKO MASTIKA BITUMEN GLUE

Substance / mixture mixture

UFI 1TJP-R0J4-G00G-TX1D

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### Mixture's intended use

Asphalt glue used for gluing asphalt felt papers to a concrete substrate and for gluing roofing papers with each other in multilayer waterproofing, as well as for making light-type anti-moisture and waterproofing coatings.

#### Main intended use

PC-ADH-2 Adhesives and sealants - building and construction works (except cement based adhesives)

#### Secondary uses

PC-CON-5 Construction chemicals

#### Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

**1.3. Details of the supplier of the safety data sheet**

#### Distributor

Name or trade name	UAB „Kesko Senukai Lithuania“
Address	Islandijos pl. 32B, Kaunas, 51500 Lithuania
Phone	8 700 11 119
Web address	www.senukai.lt

#### Supplier

Name or trade name	IZOHAN sp. z o.o.
Address	Łużycka 2, Gdynia, 81-963 Poland
Identification number (CRN)	191528483
VAT Reg No	PL5862073821
Phone	+48 58 781 45 85
E-mail	info@izohan.eu
Web address	www.izohan.eu

#### Competent person responsible for the safety data sheet

Name	IZOHAN sp. z o.o.
E-mail	info@izohan.eu

**1.4. Emergency telephone number**

National Health Service (NHS) 111  
National poisoning information centre Scotland, NHS 24: 111

### SECTION 2: Hazards identification

**2.1. Classification of the substance or mixture**

#### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 3, H226  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
STOT RE 2, H373

Full text of all classifications and hazard statements is given in the section 16.

#### Most serious adverse physico-chemical effects

Flammable liquid and vapour.

#### Most serious adverse effects on human health and the environment

May cause damage to organs through prolonged or repeated exposure. Causes serious eye irritation. Causes skin irritation.

# SAFETY DATA SHEET

**IZUHAN**

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date 22nd February 2023  
Revision date 21st April 2023 Version 1.1

### 2.2. Label elements

#### Hazard pictogram



#### Signal word

Warning

#### Hazardous substances

reaction mass of ethylbenzene and xylene

#### Hazard statements

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P264 Wash hands and exposed parts of the body thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P501 Dispose of contents/container according to the instructions of the manufacturer or person authorized to dispose of waste.

#### Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
EC: 905-588-0 Registration number: 01-2119488216-32	reaction mass of ethylbenzene and xylene	8-10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	1, 2
Index: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 Registration number: 01-2119471310-51	toluene	0,8-1,1	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2, H361d STOT RE 2, H373 (central nervous system) (inhalation) Aquatic Chronic 3, H412	1, 3

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date	22nd February 2023	Version	1.1
Revision date	21st April 2023		

### Notes

- 1 A substance for which exposure limits are set.
- 2 Substance for which biological limit values exist.
- 3 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

#### If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

Not expected.

#### If on skin

Causes skin irritation.

#### If in eyes

Causes serious eye irritation.

#### If swallowed

Irritation, nausea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

##### Unsuitable extinguishing media

Water - full jet.

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

#### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date 22nd February 2023  
Revision date 21st April 2023 Version 1.1

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Prevent contact with skin and eyes.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Keep container tightly closed. Keep cool.

#### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

#### 7.3. Specific end use(s)

not available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### United Kingdom

#### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Type	Value	Note
Xylene, o-,m-,p- or mixed isomers	WEL 8h	220 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
	WEL 8h	50 ppm	
	WEL 15min	441 mg/m <sup>3</sup>	

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date

22nd February 2023

Revision date

21st April 2023

Version

1.1

### United Kingdom

### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Substance name (component)	Type	Value	Note
Xylene, o-,m-,p- or mixed isomers	WEL 15min	100 ppm	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
ethylbenzene	WEL 8h	441 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
	WEL 8h	100 ppm	
	WEL 15min	552 mg/m <sup>3</sup>	
	WEL 15min	125 ppm	
toluene (CAS: 108-88-3)	WEL 8h	191 mg/m <sup>3</sup>	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
	WEL 8h	50 ppm	
	WEL 15min	384 mg/m <sup>3</sup>	
	WEL 15min	100 ppm	

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date	22nd February 2023	Version	1.1
Revision date	21st April 2023		

### Biological limit values

#### United Kingdom

#### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Name	Parameter	Value	Tested material	Time of sampling
reaction mass of ethylbenzene and xylene	Methylhippuric acids	650 mmol/mol creatinine	Urine	End of shift

### DNEL

reaction mass of ethylbenzene and xylene					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	442 mg/m <sup>3</sup>	Acute effects systemic		
Workers	Inhalation	442 mg/m <sup>3</sup>	Acute effects local		
Workers	Dermal	212 mg/kg bw/day	Chronic effects systemic		
Workers	Inhalation	221 mg/m <sup>3</sup>	Chronic effects local		
Workers	Inhalation	221 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Inhalation	260 mg/m <sup>3</sup>	Acute effects systemic		
Consumers	Inhalation	260 mg/m <sup>3</sup>	Acute effects local		
Consumers	Dermal	125 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	65.3 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Inhalation	65.3 mg/m <sup>3</sup>	Chronic effects local		
Consumers	Oral	12.5 mg/kg bw/day	Chronic effects systemic		

toluene					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Dermal	384 mg/kg bw/day	Chronic effects systemic		
Workers	Inhalation	192 mg/m <sup>3</sup>	Chronic effects systemic		
Workers	Inhalation	192 mg/m <sup>3</sup>	Chronic effects local		
Workers	Inhalation	384 mg/m <sup>3</sup>	Acute effects systemic		
Consumers	Dermal	226 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	56.5 mg/m <sup>3</sup>	Chronic effects systemic		
Consumers	Oral	8.13 mg/kg bw/day	Chronic effects systemic		
Consumers	Inhalation	226 mg/m <sup>3</sup>	Acute effects local		
Workers	Inhalation	384 mg/m <sup>3</sup>	Acute effects local		
Consumers	Inhalation	226 mg/m <sup>3</sup>	Acute effects systemic		
Consumers	Inhalation	56.5 mg/m <sup>3</sup>	Chronic effects local		

### PNEC

reaction mass of ethylbenzene and xylene			
Route of exposure	Value	Value determination	Source
Drinking water	0.327 mg/l		

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date 22nd February 2023  
Revision date 21st April 2023 Version 1.1

reaction mass of ethylbenzene and xylene			
Route of exposure	Value	Value determination	Source
Marine water	0.327 mg/l		
Freshwater sediment	12.46 mg/kg of dry substance of sediment		
Sea sediments	12.46 mg/kg of dry substance of sediment		
Soil (agricultural)	2.31 mg/kg of dry substance of soil		
Water (intermittent release)	0.327 mg/l		
Microorganisms in sewage treatment	6.58 mg/l		

toluene			
Route of exposure	Value	Value determination	Source
Drinking water	0.68 mg/l		
Marine water	0.68 mg/l		
Soil (agricultural)	2.89 mg/kg of dry substance of soil		
Freshwater sediment	16.39 mg/kg of dry substance of sediment		
Microorganisms in sewage treatment	13.61 mg/l		
Water (intermittent release)	0.68 mg/l		
Sea sediments	16.39 mg/kg of dry substance of sediment		

### 8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

Protective goggles.

#### Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

#### Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

#### Thermal hazard

Not available.

#### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state liquid  
Colour black  
Odour irritating

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date 22nd February 2023  
Revision date 21st April 2023 Version 1.1

Melting point/freezing point <-20 °C  
Boiling point or initial boiling point and boiling range ≥110 °C  
Flammability Flammable liquid and vapour.  
Lower and upper explosion limit not determined  
Flash point 31-40 °C  
Auto-ignition temperature not determined  
reaction mass of ethylbenzene and xylene 432-528 °C  
toluene (CAS: 108-88-3) 480 °C  
Decomposition temperature not applicable  
pH non-soluble (in water)  
Kinematic viscosity >20.5 mm<sup>2</sup>/s at 40 °C  
Solubility in water insoluble  
Solubility in other solvents dissolves in most organic solvents  
Partition coefficient n-octanol/water (log value) does not apply to mixtures  
Vapour pressure not determined  
reaction mass of ethylbenzene and xylene 6.5-9.5 hPa at 20 °C  
toluene (CAS: 108-88-3) 30.9 hPa at 21.1 °C  
Density and/or relative density  
Density 1.3-1.5 g/cm<sup>3</sup> at 22 °C  
Relative vapour density >1  
Particle characteristics applies to solids

### 9.2. Other information

not available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The mixture is not reactive.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Unknown.

### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Not developed under normal uses.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### Acute toxicity

Based on available data the classification criteria are not met.

#### reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	EU B.1	3523 mg/kg bw		Rat	M
Inhalation (vapor)	LC <sub>50</sub>	EU B.2	27124 mg/m <sup>3</sup>	4 hours	Rat	M
Skin	LD <sub>50</sub>		12126 mg/kg bw		Rabbit	M



# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date 22nd February 2023  
Revision date 21st April 2023 Version 1.1

toluene						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD <sub>50</sub>	EU B.1	5580 mg/kg bw		Rat ( <i>Rattus norvegicus</i> )	M
Dermal	LD <sub>50</sub>		>5000 mg/kg bw	24 hours	Rabbit	
Inhalation (vapor)	LC <sub>50</sub>	OECD 403	>20 mg/l of air	4 hours	Rat ( <i>Rattus norvegicus</i> )	F/M

### Skin corrosion/irritation

Causes skin irritation.

reaction mass of ethylbenzene and xylene				
Route of exposure	Result	Method	Exposure time	Species
Dermal	Irritating	EU B.4	4 hours	Rabbit

toluene				
Route of exposure	Result	Method	Exposure time	Species
Dermal	Irritating	EU B.4	4 hours	Rabbit

### Irritation

reaction mass of ethylbenzene and xylene			
Route of exposure	Result	Exposure time	Species
Inhalation	Irritating		

### Serious eye damage/irritation

Causes serious eye irritation.

reaction mass of ethylbenzene and xylene				
Route of exposure	Result	Method	Exposure time	Species
Eye	Irritating			Rabbit

toluene				
Route of exposure	Result	Method	Exposure time	Species
Eye	Slightly irritating	OECD 405		Rabbit

### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

### Germ cell mutagenicity

Based on available data the classification criteria are not met.

### Carcinogenicity

Based on available data the classification criteria are not met.

### Reproductive toxicity

Based on available data the classification criteria are not met.

### Toxicity for specific target organ - single exposure

Based on available data the classification criteria are not met.

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date 22nd February 2023  
Revision date 21st April 2023 Version 1.1

### Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure. Based on available data the classification criteria are not met.

### Repeated dose toxicity

#### reaction mass of ethylbenzene and xylene

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	EU B.32	250 mg/kg bw/day	103 weeks	Rat (Rattus norvegicus)	F/M
Inhalation (vapor)	NOAEC	Systemic effects		3515 mg/m <sup>3</sup>	13 weeks	Dog	M

#### toluene

Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL	Systemic effects	EU B.26	625 mg/kg bw/day	13 weeks	Rat (Rattus norvegicus)	F/M
Inhalation (vapor)	NOAEC	Systemic effects	OECD 453	98 mg/m <sup>3</sup>	1 year	Rat (Rattus norvegicus)	F/M
Inhalation (vapor)	LOAEC	Local effects	EU B.29	2261 mg/m <sup>3</sup>	15 weeks	Rat (Rattus norvegicus)	F/M

### Aspiration hazard

Based on available data the classification criteria are not met.

### 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 12: Ecological information

### 12.1. Toxicity

not available

#### Acute toxicity

#### reaction mass of ethylbenzene and xylene

Parameter	Method	Value	Exposure time	Species	Environment
LC <sub>50</sub>	OECD 203	2.6 mg/l	96 hours	Fish (Oncorhynchus mykiss)	
EC <sub>50</sub>	OECD 201	2.2 mg/l	73 hours	Algae (Pseudokirchneriella subcapitata)	
EC <sub>50</sub>	OECD 209	>157 mg/l	3 hours	Aquatic microorganisms	Activated sludge
NOEC	OECD 201	0.44 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)	
IC <sub>50</sub>		220 mg/kg of dry substance of soil	10 hours	Microorganisms	
EC <sub>50</sub>	OECD 202	1 mg/l	24 hours	Aquatic invertebrates (Daphnia magna)	

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date	22nd February 2023	Version	1.1
Revision date	21st April 2023		

toluene					
Parameter	Method	Value	Exposure time	Species	Environment
LC <sub>50</sub>		5.5 mg/l	96 hours	Fish (Oncorhynchus kisutch)	
EC <sub>50</sub>		3.78 mg/l	48 hours	Aquatic invertebrates (Ceriodaphnia dubia)	
EC <sub>50</sub>	OECD 201	134 mg/l	3 hours	Algae (Selenastrum capricornutum)	
NOEC	OECD 201	10 mg/l	72 hours	Algae (Skeletonema costatum)	
IC <sub>50</sub>		84 mg/l	24 hours	Aquatic microorganisms (Nitrosomonas)	

### Chronic toxicity

reaction mass of ethylbenzene and xylene					
Parameter	Method	Value	Exposure time	Species	Environment
NOEC		>1.3 mg/l	56 days	Fish (Salmo gairdneri)	
NOEC		0.96 mg/l	7 days	Aquatic invertebrates (Ceriodaphnia dubia)	
NOEC	OECD 301F	16 mg/l	28 days	Aquatic microorganisms	Activated sludge
NOEC		16 mg/kg of dry substance of soil	14 weeks	Invertebrates (Eisenia andrei)	

toluene					
Parameter	Method	Value	Exposure time	Species	Environment
NOEC		1.4 mg/l	40 days	Fish (Oncorhynchus kisutch)	
NOEC		0.74 mg/l	7 days	Aquatic invertebrates (Ceriodaphnia dubia)	

### 12.2. Persistence and degradability

The product is partially biodegradable.

#### Biodegradability

reaction mass of ethylbenzene and xylene				
Parameter	Value	Exposure time	Environment	Result
				Easily biodegradable

toluene				
Parameter	Value	Exposure time	Environment	Result
				Easily biodegradable

### 12.3. Bioaccumulative potential

Bioaccumulation is not expected.

reaction mass of ethylbenzene and xylene					
Parameter	Value	Exposure time	Species	Environment	Temperature [°C]
BCF	25.9				

# SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date 22nd February 2023  
Revision date 21st April 2023 Version 1.1

### reaction mass of ethylbenzene and xylene

Parameter	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	3.16				20°C

### toluene

Parameter	Value	Exposure time	Species	Environment	Temperature [°C]
Log Pow	2.73				20°C

#### 12.4. Mobility in soil

The product is insoluble in water and does not show mobility in soil.

### reaction mass of ethylbenzene and xylene

Parameter	Method	Value	Environment	Temperature
Log Koc	OECD 121	2.73		

### toluene

Parameter	Method	Value	Environment	Temperature
Koc		205		20°C

#### 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

#### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

#### 12.7. Other adverse effects

Not available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Danger of environmental contamination, follow the applicable waste disposal regulations. Store unused product and contaminated packaging in closed containers for waste collection and hand over for disposal to a specialized company authorized to conduct such activity. Do not pour unused product into drains. It must not be disposed of together with municipal waste. Empty packaging can be used for energy in a waste incineration plant or collected in a landfill with an appropriate classification. Perfectly cleaned packaging can be recycled. The classification of waste may change depending on where it is generated.

#### Waste management legislation

Producer Responsibility Obligations (Packaging Waste) Regulations 2007 (S.I. No. 871 of 2007). Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

### SECTION 14: Transport information

#### 14.1. UN number or ID number

UN 1993

#### 14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (contains: reaction mass of ethylbenzene and xylene)

#### 14.3. Transport hazard class(es)

3 Flammable liquids

#### 14.4. Packing group

III - substances presenting low danger

#### 14.5. Environmental hazards

No.

# SAFETY DATA SHEET

**IZUHAN**<sup>®</sup>

according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date	22nd February 2023	Version	1.1
Revision date	21st April 2023		

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### Additional information

NOTE: The product packed in receptacles with a capacity of not more than 450 liters is not subject to the provisions of ADR (2.2.3.1.5).

Hazard identification No.

**30**

UN number

**1993**

Classification code

F1

Safety signs

3



### Marine transport - IMDG

EmS (emergency plan)

F-E, S-E

MFAG

310

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Clean Air Act 1993 as amended. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 as amended. Public health act 1961. Environmental Protection Act 1990 as amended. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

toluene

Restriction	Conditions of restriction
48	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

## SECTION 16: Other information

### A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date	22nd February 2023	Version	1.1
Revision date	21st April 2023		

- H373 May cause damage to the central nervous system through prolonged or repeated exposure if inhaled.
- H412 Harmful to aquatic life with long lasting effects.
- H312+H332 Harmful in contact with skin or if inhaled.

### Guidelines for safe handling used in the safety data sheet

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P264 Wash hands and exposed parts of the body thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P501 Dispose of contents/container to according to the instructions of the manufacturer or person authorized to dispose of waste.

### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

### Key to abbreviations and acronyms used in the safety data sheet

- ADR European agreement concerning the international carriage of dangerous goods by road
- BCF Bioconcentration Factor
- CAS Chemical Abstracts Service
- CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
- EC Identification code for each substance listed in EINECS
- EC<sub>50</sub> Concentration of a substance when it is affected 50% of the population
- EINECS European Inventory of Existing Commercial Chemical Substances
- EmS Emergency plan
- EU European Union
- EuPCS European Product Categorisation System
- IATA International Air Transport Association
- IBC International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
- IC<sub>50</sub> Concentration causing 50% blockade
- ICAO International Civil Aviation Organization
- IMDG International Maritime Dangerous Goods
- IMO International Maritime Organization
- INCI International Nomenclature of Cosmetic Ingredients
- ISO International Organization for Standardization
- IUPAC International Union of Pure and Applied Chemistry
- LC<sub>50</sub> Lethal concentration of a substance in which it can be expected death of 50% of the population
- LD<sub>50</sub> Lethal dose of a substance in which it can be expected death of 50% of the population
- LOAEC Lowest observed adverse effect concentration
- log K<sub>ow</sub> Octanol-water partition coefficient
- NOAEC No observed adverse effect concentration
- NOAEL No observed adverse effect level
- NOEC No observed effect concentration
- OEL Occupational Exposure Limits
- PBT Persistent, Bioaccumulative and Toxic
- ppm Parts per million
- REACH Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID Agreement on the transport of dangerous goods by rail
- UN Four-figure identification number of the substance or article taken from the UN Model Regulations
- UVCB Substances of unknown or variable composition, complex reaction products or biological materials

# SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

## BRIKO MASTIKA BITUMEN GLUE

Creation date	22nd February 2023	Version	1.1
Revision date	21st April 2023		

VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

This safety data sheet replaces version 1.0 dated 22.02.2023.  
Updated sections: 1,2,3,4,7,8,9,11,12,14,15,16.

### More information

Classification procedure - calculation method and based on tests of physicochemical properties.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.