



NEXLER STYROPUK Polyurethane Foam Cleaner

TECHNICAL DATA

Composition	mixture of organic solvents
Time to remove soiling	5 - 30 s
Ambient and substrate temperature during application	from +5°C to +35°C
Can temperature	from +10°C to +25°C
Storage temperature	from +5°C to +25°C

PROPERTIES


- Quickly dissolves uncured residues of one-component polyurethane products
- Does not leave a sticky film
- Does not contain freon



FOR GUN CLEANING



FOR SURFACE CLEANING



FOR REMOVING UNCURED PU FOAM



FOR DEGREASING STEEL SURFACES

APPLICATION

- Removal of uncured polyurethane foams and adhesives
- Cleaning of container valves, nozzles and guns dispensing polyurethane foam
- Degreasing steel surfaces prior to applying polyurethane and silicone materials



CLOTH



PROTECTIVE GLOVES

PACKAGING

Poland

- Can: 500 ml
- Quantity per box: - 500 ml - 12 pcs.

Export

- Can: 500 ml
- Quantity per box: - 500 ml - 12 pcs.

METHOD OF USE

CONDITIONS OF USE

The temperature of the substrate and air during the works should be from +5°C to +35°C.

PRODUCT CONTROL

Check the production date on the packaging before use. Product packaging must not show signs of damage.

PRODUCT PREPARATION

STYROPUK Polyurethane Foam Cleaner is a ready-to-use product. Before spraying the product, place the spray head located at the valve on the valve.

APPLICATION

Cleaning of soiling: For surfaces soiled with foams or polyurethane adhesives, spray the fresh stains with **STYROPUK Polyurethane Foam Cleaner** from a distance of 25 - 35 cm. Then, after a period of 5 to 30 seconds, remove the soiling with a dry cloth. In case of heavy soiling, the operation can be repeated.

In order to clean the outlet of the container soiled with polyurethane foam, **STYROPUK Polyurethane Foam Cleaner** should be thoroughly sprayed onto the valve and gun adapter. Remove soiling with a dry cloth as well.

Cleaning of the gun: First, disconnect the gun from the polyurethane foam container. Remove any remaining foam in the gun by pressing the gun lever. Then screw **STYROPUK Polyurethane Foam Cleaner** onto the gun, squeeze the trigger and fill with cleaning agent. After 10 minutes (no later than after 15 minutes), press the gun lever several times until the gun is completely clean of foam. Unscrew **STYROPUK Polyurethane Foam Cleaner** and wipe the excess cleaner off the adapter. All cleaned surfaces must be thoroughly dried.

It is essential to unscrew **STYROPUK Polyurethane Foam Cleaner** from the gun after the cleaning process to avoid damaging the seals in the gun. Never clean the gun with water and never disassemble the unit for cleaning.

STORAGE AND TRANSPORT

The shelf life of the product is 36 months from production date. Store in dry and cool rooms equipped with mechanical ventilation, at a temperature of +5°C to +25°C. Store upright, in tightly sealed, original packaging. The product must be protected against being heated to a temperature of above +50°C and against direct sunlight.

NOTES

Works should be carried out in accordance with technical conditions, manufacturer's instructions, health and safety standards and regulations. For information on how to deal with symptoms of disease, allergies or irritation of the skin or eyes, please refer to the Safety Data Sheet (www.nexler.com).

The remaining content of the product and container should be handed over to authorized companies.

GENERAL RECOMMENDATIONS

Pressurised container. Do not use the product in enclosed spaces. Do not use on polystyrene foam or materials not resistant to organic solvents. Do not pierce or burn the can, even after use. Do not spray over an open flame or glowing material.

SAFETY INFORMATION

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Dispose of contents/container according to the instructions of the manufacturer or person authorized to dispose of waste.

IMPORTANT INFORMATION

Please refer to the detailed conditions of use of the product before use. We guarantee the quality of our materials as part of our terms of sale and delivery.

For buildings with special requirements that are not covered by this manual, we provide our Customers with our own professional advisory service.

The manufacturer has no influence on the improper use of the material, its use for other purposes or under conditions other than those described above. The guarantee only covers the quality of the delivered product. The correct and therefore effective use of the product is not subject to our control.

Neither the manufacturer nor his authorized representative may be held liable for any loss incurred as a result of improper use or storage of the product.

Employees of the company are authorized to provide technical information only and solely in accordance with this technical data sheet. Information other than that contained in this sheet should be confirmed in writing.

If you have any doubts, consult the manufacturer.

Once we have issued a new technical data sheet, this manual is no longer valid.

CONTACT DETAILS

NEXLER sp. z o.o.

Łużycka 6, 81-537 Gdynia, Poland

tel.: +48 58 712 94 44

www.nexler.com

e-mail: dt@nexler.com