

**NATIONAL DECLARATION OF PERFORMANCE
No. 727-KDWU-2021**

1. *Name and trade name of the construction product:*
Name: venting asphalt perforated roofing felt NEXLER Izolvent
Trade name: NEXLER Izolvent
2. *Identification of the type of the construction product:*

venting asphalt roofing felt
NEXLER Izolvent
IMBiGS – KOT – 2021/0029 wydanie 1

3. *Intended use or uses:*
NEXLER Izolvent asphalt roofing felt is intended for making a ventilation layer in multi-layer roof coverings. The roofing felt is laid loosely on the substrate, point fixing to the substrate is made through the perforation during mounting of the proper waterproofing.
4. *Name and address of the manufacturer:*

NEXLER sp. z o.o.
ul. Łużycka 6, 81-537 Gdynia, Poland
tel., fax +48 58 781 45 85
www.nexler.com

Production site:
Poland

5. *Name and address of authorised representative, where applicable:*
not applicable
6. *National system applied for assessment and verification of constancy of performance:*
3

7. *National technical specification:*

7a. *Polish product standard:* not applicable

Name of accredited certification body, number of accreditation and number of national certificate or name of accredited laboratory/laboratories and number of accreditation: not applicable

7b. *National Technical Assessment:* Krajowa Ocena Techniczna IMBiGS – KOT – 2021/0029 issue 1
Technical Assessment Body/National Technical Assessment Body: Sieć Badawcza Łukasiewicz - Instytut Mechanizacji Budownictwa i Górnictwa Skalnego, ul. Racjonalizacji 6/8, 02-673 Warszawa, Dział ds. Ocen Technicznych, al. W. Korfantego 193 A, 40-157 Katowice

Name of accredited certification body, number of accreditation and number of certificate: not applicable

8. *Declared performance:*


<i>Essential characteristics of construction product for the intended use or uses</i>	<i>Declared performance</i>	<i>Remarks</i>
Fire classification	class E	
Concentration of natural radioactive elements		
- f ₁	≤ 1	
- f ₂ , Bq/kg	≤ 185	
Chloroform-soluble components content, g/m ²	≥ 750	
Temperature resistance at 70°C for 2 h	unacceptable mass flow	
Flexibility at 0°C temperature		
-top side	no cracks	
-bottom side	no cracks	

9. *The performance of the product identified above is in conformity with all declared performance in clause 8. This national declaration of performance is issued in accordance with the act on construction products dated 16 April 2004 under the sole responsibility of the manufacturer.*

Signed for and on behalf of the manufacturer by:

Dawid Dębski, R&D Manager
(name and function)

Gdynia, 31.01.2024, issue 3
(place and date of issue)

dyrektor ds. badań

.....
dr inż. Dawid Dębski
(signature)