



DECLARATION OF PERFORMANCE No. 240-CPR-2024

1. Unique identification code:

Heat-weldable top layer bitumen membrane

NEXLER PREMIUM PYE PV 50H (2024/1)

2. Intended use or uses:

- waterproofing of roofs, which is the subject to fire reaction test,
- waterproofing of roofs,

3. The manufacturer:

NEXLER sp. z o.o.
ul. Łużycka 6, 81-537 Gdynia, Poland
tel., fax +48 58 781 45 85
e-mail: info@nexler.com

4. Systems of assessment and verification of constancy of performance:

system 2+ – for the applications: b
system 3 – for the applications: a

5. Harmonized standard:

EN 13707:2004+A2:2009

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification
(Polskie Centrum Badań i Certyfikacji S.A.)

1487 Institute of Ceramics and Building Materials
(Instytut Ceramiki i Materiałów Budowlanych).

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Resistance to external fire exposure	NPD	EN 13707:2004+A2:2009
Reaction to fire	class E	
Watertightness	≥ 10 kPa (method A)	
Maximum tensile force: - longitudinal - extension	800 ± 200 N/50 mm (50 ± 25) %	
- transverse - extension	600 ± 200 N/50 mm (50 ± 25) %	
Resistance to root penetration	NPD	
Resistance to static loading	NPD	
Resistance to impact	NPD	
Tear resistance	NPD	
Joint strength	NPD	
Durability: flow resistance in high temperature	(100 ± 10) °C	
Flexibility	≤ -20 °C	
Dangerous substances	NPD	

The performances of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no. 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Konrad Liberda


Kierownik Biura Produktowej
Wsparcia Technicznego
Konrad Liberda

Gdynia, 23.03.2024

