

**DECLARATION OF PERFORMANCE**  
**No. 804-CPR-2024**

1. Unique identification of the product-type:  
**NexGreen Duo BB 20/150 P 01**

2. Intended use/es:  
**For filtration and drainage (F + D) in drainage systems.**

3. Manufacturer:  
**NEXLER sp. z o.o.**  
**ul. Łużycka 6, 81-537 Gdynia, Polska**  
**tel., fax +48 58 781 45 85**  
**www.nexler.com**

4. System/s of AVCP:

**System 2+**

5. Harmonised standard:

**EN 13252:2016**

Notified body/ies:

**Polskie Centrum Badań i Certyfikacji S.A., nr 1434**

6. Declared performance/es:

Essential characteristics	Performance of the product
Tensile strength -MD -CMD	10,1 kN/m, -2,8 kN/m 12,3 kN/m, -2,5 kN/m
Elongation at maximum load -MD -CMD	74, ± 35% 58, ± 30%
Dynamic perforation resistance	31 mm, +6 mm
Characteristic opening size	170 µm, ± 51 µm
Water permeability normal to the plane	145 l/(m <sup>2</sup> s), -43 l/(m <sup>2</sup> s)
Water flow capacity in the plane	NPD
Durability - resistance to weathering  - durability	To be covered within one day after installation.  Predicted to be durable a minimum of 5 years for non-reinforcing applications in natural soils with 4 ≤ pH ≤ 9 and soil temperatures ≤ 25 °C.
Dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Dawid Dębski at Gdynia on 06.06.2024. (1st issue)

  
**Dyrektor ds. Badań i Rozwoju**  
  
dr inż. Dawid Dębski